IBEX Command Approval Checklist Rev 16b incorporates post-ST anomaly changes and resetting the SSR pointers in an APL contact.

Orbit	399	Special Ops	ISN Pointing			
14 R _E asc. Date/Time	3/3/2018 08:4	43:08	15 R _E asc. Date/Time	3/3/2018 10:1	7:40	
Apogee	3/7/2018 08:40:36	Maneuver Window Start	3/6/2018 22:36:32	Maneuver Window End	3/7/2018 18:36:34	
Apogee Target	targetX:0.9768080000000001 targetY:-0.1924569999999999999 targetZ:-0.0938480000000000					
15 R _E desc. Date/Time	3/11/2018 07	:15:13	14 R _E desc. Date/Time	3/11/2018 08:49:30		
Perigee	3/11/2018 19:03:34	Maneuver Window Start	3/11/2018 09:15:08	Maneuver Window End	3/12/2018 05:13:17	
Perigee Target	targetX:0.9903 targetZ:-0.064		/ targetY:-0.1230)1600000000000000000		
Eclipse	No	Eclipse Start		Eclipse End		
Sun Mnvr	No	Apogee/Perigee		Sun Angle at DESCENDING		
Approved Version	IBEX_2018_061	_00399a_v001.s	scr			

Activity	Command Checks	Date Done	Done By
Supporting Materials	 IBEX_CrossingTimes_<date>_v00x.txt on SFTP at /IBEX/fdg/PredictedEphemeris/Orbit Events/.</date> Orbit Events File on SFTP at /IBEX/moc/Moc-Soc/oef/. Command Constraint Violations Report on SFTP at /IBEX/moc/Moc-Soc/cvr/. Contacts this orbit Orbit_oXXX.txt included in the ATS approval email. Science Tasking File at /IBEX/moc/Soc-Moc/stf/. Merged ATS at http://ibex.unh.edu/cgi-bin/ats.cgi. 	02/20/18 Orbit 399 commands not in merged ATS	NGA
Sun Maneuvers	 Additional contacts <i>should not</i> be planned to support IBEX Sun Precession Maneuvers due to star tracker outages. The standard apogee and perigee contacts should be used to verify that a maneuver has occurred. If it is not possible to plan one of the standard contacts after the star tracker outage is down to 50% and a valid quaternion reading can be made to verify the maneuver, the coarse Sun sensor angle and the thruster pulse count will be used to determine a) whether a maneuver took place, and b) whether the pointing after the maneuver is as expected +/- 2 degrees. The nominal off-Sun pointing constraint is 7.25 degrees. Based on the missed maneuver in orbit 114, the payload team has determined that there is no hardware risk associated with off-Sun pointing up to angles of at least 13 degrees. There is a higher background noted in the data starting at around 9.5 degrees off Sun pointing. 	N/A	NGA
File Input Check	 Current OEF inputs are Forecast STF, last orbit's OEF & latest ephemeris. ATS inputs are this orbit's OEF & STF. (And ABS if present.) ATS filename is of the format IBEX_yyyy_doy_00xxxa_v0zz.scr. where IBEX is capitalized, yyyy is the year, doy is the day of year, xxx is the 3-digit orbit number and zz is the 2-digit version number. Any special operations ATSs will have another designation between the orbit number and version number (i.e. *00186a hgc v001 for the Hi gain curve). 	02/20/18	NGA

	1. Check OEF for eclipses during the orbit.	27/1	
Eclipses	 Check OEF for eclipses during the orbit. Verify long eclipse flag start & stop times reflect Ryan Tyler's recommendations based on his eclipse diagnostic tool. Suggestions made by Ryan after the use of this tool trump the general guidelines below. (Please note, specific timing may shift if the recommendations are relative to eclipse timing. For example, it may say set LE flag to false X hours after the end of the eclipse with a given FALSE time suggested. If the eclipse timing changes as the ephemeris becomes more refined, this command time may shift.) Verify no contacts planned during an eclipse. Note: If in conflict, the eclipse diagnostic recommendations will trump the general guidelines below. a Verify transmitter OFF from 30 minutes before eclipse start through the end of the eclipse. b For an eclipse where the long eclipse flag is set, schedule a SOH contact directly following the end of the eclipse. Note: If in conflict, the eclipse diagnostic recommendations will trump the general guidelines below. Verify no maneuver planned during an eclipse. Note: If in conflict, the eclipse diagnostic recommendations will trump the general guidelines below. a Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through 3 hours after eclipse end. b Verify no maneuver or cat bed heaters are on while the long eclipse flag is set. Verify the following additional constraints (from battery balancing section). a Verify P/L is in HVSTANDBY or HVENG. c Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution. This applies to all eclipses, not just moderate or long eclipses. 	N/A	NGA
Moon In Lo FOV	 This applies to all eclipses, not just moderate or long eclipses. Check OEF for Moon in Lo FOV events. MoonInLoFovStart 3/10/2018 13:42:40 MoonInLoFovStop 3/11/2018 03:43:22 Check for corresponding Moon in Lo FOV start commands in ATS (timing will not be exact). PMT_LVL 300 \$TIME=2018/03:10:11:16:59 IF_STAR_ADJ 0 \$TIME=2018/03:10:11:17:01 Note: if the Moon is closer than 30Re, the PMT will be set to 250. The distance to the moon can be found in the STF. Check for corresponding Moon in Lo FOV stop commands. IF_STAR_ADJ 250 \$TIME=2018/03:10:23:00:31 PMT_LVL 800 \$TIME=2018/03:10:23:00:33 Note: if the Moon is still in the FOV at the time of DESCENDING, no Moon in Lo FOV stop commands will be present in ATS. The values are reset to the default at next set of ASCENDING macros. If Moon in Lo FOV starts in arc a & ends in arc b, check Moon in Lo FOV Start commands resent after apogee ASCENDING commands. If Moon in Lo FOV starts within apogee HVSTANDBY period, check Moon in Lo FOV Start commands sent after apogee ASCENDING commands. 	02/20/18	NGA

Contact	1. Each contact has 5 commands.	02/20/18	NGA
Contact Commands		02/20/18	NGA
Commands	1. Verify STX on/off times, downlink rate against <i>Orbit_oXXX.txt</i> file.		
	2. Verify contacts in the previous ATS have not been duplicated.		
	Verify all currently planned contacts in Orbit_xxx.txt are in the ATS.		
	Verify each contact contains the following 5 commands.		
	SetRelay stx,on		
	 SetDownlink2K (2K, 40K, 64K, 160K, or 320K) 		
	 SetBilevelOutputControlReg STXMODE_Strobe,ON 		
	SetBilevelOutputControlReg COHERENT,ON		
	SetRelay stx,off		
	5. If contact is near an eclipse		
	 Verify transmitter OFF from 30 minutes before eclipse start through 30 minutes after eclipse end. 		
	b. If additional transmitter constraints exist, they will be captured in Ryan's recommendations.		
	6. If an APL contact is being used for an SSR Dump, the data rate should be at least 160 ksps & the SSR		
	DUMP_NEW command should be included in the contact commands. Commands in Orange should only		
	be sent if the SSR pointers need to be reset this perigee. These commands should be separated by 2s and		
	occur 2s after the SSR_DUMP_NEW command.		
	SetRelay stx,on		
	• SetDownlink2K		
	SetBilevelOutputControlReg STXMODE_Strobe,ON		
	SetBilevelOutputControlReg COHERENT,ON		
	SetDownlink320K		
	SSR_DUMP_NEW		
	• SSR_SET_RD_PTR 6500		
	• SSR_SET_WRT_PTR 6500		
	SetRelay stx,off		
SC State	1. Transition to Science state will be first command of each ATS (at 14 Re).	02/20/18	NGA
Science: arc	 SetScState science \$TIME=2018/03:03:08:43:16 		
а	2. Lo science mode will be the next command (at 14 Re).		
	• LO_SCIENCE_MODE NORMAL		
	3. Verify no transition to Science again at the end of the ATS. The ATS commands go from 14 Re to 14 Re		
	in each orbit.		
	4. Verify the transition to Science commands for this orbit are not part of the previous ATS using		
	http://ibex.unh.edu/cgi-bin/ats.cgi.		
	5. Verify that the beginning of this ATS does not overlap with the end of the previous orbit's ATS using		
	http://ibex.unh.edu/cgi-bin/ats.cgi.		
Payload	1. Verify w/ Crossing Times report that it occurs about 15Re ascending. The arc a ASCENDING commands	02/20/18	NGA
Mode	can start any time at or above 15Re ascending.	02/20/10	NUA
HVSCI :	2. Verify commanding takes ~ 24 minutes.		
arc a	 ASCENDING_PL1 \$TIME=2018/03:03:10:17:44 		
	ASCENDING_HI		
	 SET_PARAMETER 1, TLM_RATE_SOH 		
	 SET_PARAMETER 4, HV_STEP_DWELL 		
	 SET_PARAMETER 3, HV_STEP_FRAC 		
	HI_COL_NEG_LVL 1400		
	• CEU_HI_CEM_1_LVL 1780		
	• CEU_HI_CEM_2_LVL 1780		
	• CEU_HI_CEM_3_LVL 1780		
	• CEU_HI_CEM_4_LVL 1900		
	• SET_PARAMETER 0, TLM_RATE_SOH		
			1
	ASCENDING_PL2 ASCENDING_PL1		
	ASCENDING_PL1		

Payload Mode		1. Payload DESCENDING commands end 1.5h before thruster enable.	02/20/18	NGA
HVSTANDBY		 DESCENDING_PL1 \$TIME=2018/03:07:09:26:41 		
: arc a		DESCENDING_LO		
		ASCENDING_PL2		
		DESCENDING_PL1		
		DESCENDING_HI		
		 DESCENDING_PL2 \$TIME=2018/03:07:09:49:31 		
SC State HK :	1.	Spacecraft Housekeeping command occurs 1h before thruster enable.	02/20/18	NGA
arc a		SetScState housekeeping \$TIME=2018/03:07:10:22:41	02/20/18	NGA
Inertial	1.	Use this command sequence if an apogee inertial maneuver is used, otherwise skip to the 'Sun Precession	02/20/18	NGA
Maneuver :	2.	Maneuver : Apogee' sequence below. Verify Thruster enable command occurs within STF maneuver window.		
Apogee	2. 3.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission.	Maneuver	
		Verify cat bed heaters come on 55 min before burn.	delayed due	
	4.	CATBED_5N_HTR,ON \$TIME=2018/03:07:10:28:21	to star	
	5.	Verify Kalman Filter input select is ground command & estimator update is disabled.	tracker	
	5.	 SetKFInputSelect GND_CMD, 0, 0, 0, 0 	outage	
		SetEstUpdateEnables ENABLE, DISABLE		
	6.	Verify in FC mode Burn.		
	0.	SetFcMode burn		
	7.	Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match.		
	1.	 SetInrDir III ATS with pointing as defined in the Porecast STP & Verify the Vectors match. SetInrDir 0.976808,-0.192457,-0.093848 		
		targetX:0.9768080000000001 targetY:-0.1924569999999999999		
		targetZ:-0.09384800000000000		
	8.	Verify inertial maneuver chosen.		
	0.	SetLrTarget ACS_INERTIAL		
	9.	Verify thrust time set to 11 min.		
	1.	SetThrustTime 660		
	10	Verify thruster enable command matches RepointingManeuverStart time in OEF.		
	10.	SetThrustEnable ENABLE \$TIME=2018/03:07:11:23:21		
		RepointingManeuverStart 2018-03-07T11:23:21		
	11	Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0.		
	11.	 SetThrustEnable DISABLE \$TIME=2018/03:07:11:33:21 		
		SetHTRCmd CATBED_5N_HTR,OFF		
	12	SetThrustTime 0 Varify 25 min after thrusters enabled: Statis 7 rate set, outgos % valid set, EC mode Mission		
	12.	Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
		SetStaticZrate ESTIMATOR, 0.418 \$TIME=2018/03:07:11:48:31		
		SetKFInputSelect STA_PCT_VALID, 43,28,33,48		
		SetFcMode Mission		

Precession Maneuver :	 Use this command sequence in the event of an apogee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC mode Mission. Verify cat bed heaters powered on 55 min before thruster enable. CATBED_5N_HTR,ON 	N/A	NGA
	 5. Verify in FC mode Burn and Sun target. SetFcMode burn 		
	SetLrTarget ACS_SUN Verify thrust time set to 16 min.		
	 SetThrustTime 960 7. Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE 		
	 SunMvrBegin 8. Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0, FC 		
	 werify 15 influtes after tillusters enabled, tillusters disabled, cat bed fleaters off, tillust tille set to 0, FC mode Mission. SetThrustEnable DISABLE 		
	 SetHTRCmd CATBED_5N_HTR,OFF SetThrustTime 0 		
	SetFcMode Mission Spacecraft Science commands occur ~1h after thruster Disable.		
SC State Science : arc b	 SetScState science \$TIME=2018/03:07:12:37:45 LO_SCIENCE_MODE NORMAL 	02/20/18	NGA
	 Verify payload ASCENDING commands begin at least 1.5 hours after thruster DISABLE. Verify commands take ~24 minutes to execute. ASCENDING_PL1 \$TIME=2018/03:07:13:07:45 ASCENDING_HI SET_PARAMETER 1, TLM_RATE_SOH SET_PARAMETER 3, HV_STEP_DWELL SET_PARAMETER 3, HV_STEP_FRAC HI_COL_NEG_LVL 1400 CEU_HI_CEM_1_LVL 1780 CEU_HI_CEM_2_LVL 1780 CEU_HI_CEM_3_LVL 1780 SET_PARAMETER 0, TLM_RATE_SOH 	02/20/18	NGA
	 ASCENDING_PL2 ASCENDING_PL1 ASCENDING_LO ASCENDING_PL2 \$TIME=2018/03:07:13:31:33 		
HVSTANDBY	 Verify w/ Crossing Times report that it occurs about 15 Re descending. The arc b DESCENDING commands can complete any time at or above 15Re descending. Verify commands take ~23 minutes to execute. 	02/20/18	NGA
. are 0	 DESCENDING_PL1 \$TIME=2018/03:11:06:49:09 DESCENDING_LO ASCENDING_PL2 DESCENDING_PL1 DESCENDING_HI DESCENDING_PL2 \$TIME=2018/03:11:07:11:59 		
SC State HK : arc b	 Verify with Crossing Times report that Transition to Housekeeping state occurs at 14 Re desc (or an hour before the maneuver if the maneuver occurs less than 1 hour after 14 Re desc). SetScState housekeeping \$TIME=2018/03:11:08:19:29 	02/20/18	NGA

Inertial	1. Use this command sequence if a perigee inertial maneuver is used, otherwise skip to the 'Sun Precession Maneuver : Perigee' sequence below.	02/20/18	NGA
Maneuver :	 Verify no eclipse occurs from cat bed heater on through set FC mode Mission. 		
Perigee	 Verify to be bed beaters come on 55 min before burn. 		
	 CATBED_5N_HTR,ON \$TIME=2018/03:11:08:20:08 		
	4. Verify in Housekeeping state.		
	 Verify Kalman Filter input select is ground command & estimator update is disabled. 		
	SetKFInputSelect GND_CMD, 0, 0, 0		
	SetEstUpdateEnables ENABLE, DISABLE		
	6. Verify in FC mode Burn.		
	SetEcMode burn		
	 Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. 		
	 SetInrDir 0.990308,-0.123016,-0.06448 		
	targetX:0.99030799999999997 targetY:-0.1230160000000000000		
	targetZ:-0.0644800000000000		
	8. Verify inertial maneuver chosen.		
	SetLrTarget ACS_INERTIAL		
	9. Verify thrust time set to 11 min.		
	SetThrustTime 660		
	10. Verify thruster enable command matches RepointingManeuverStart time in OEF.		
	SetThrustEnable ENABLE \$TIME=2018/03:11:09:15:08		
	RepointingManeuverStart 2018-03-11T09:15:08		
	11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0.		
	SetThrustEnable DISABLE \$TIME=2018/03:11:09:25:08		
	• CATBED 5N HTR,OFF		
	• SetThrustTime 0		
	12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
	 SetStaticZrate ESTIMATOR, 0.418 \$TIME=2018/03:11:09:40:18 		
	 SetStattchate LSTIMATOR, 0.418 STIME-2018/05.11.05.40.18 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 		
	 Setter inputselect 31A_FCF_VALID, 43,28,33,48 SetFcMode Mission 		
Sun	1. Use this command sequence in the event of a perigee Sun maneuver.	N/A	NGA
Precession	2. Verify Thruster enable command occurs within STF maneuver window.		
Maneuver :	 Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. 		
Perigee	 4. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON 		
	5. Verify in FC mode Burn and Sun target.		
	SetFcMode burn		
	SetLrTarget ACS_SUN		
	6. Verify thrust time set to 16 min.		
	SetThrustTime 960 Warfs thruster each a second metabox Sum Mar Design times in OEE		
	7. Verify thruster enable command matches SunMvrBegin time in OEF.		
	SetThrustEnable ENABLE		
	• SunMvrBegin		
	 Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0, FC mode Mission. 		
	SetThrustEnable DISABLE		
	SetHTRCmd CATBED_5N_HTR,OFF		
	SetThrustTime 0		
	SetFcMode Mission		
Battery Cell	1. There will be battery cell balancing every 2 out of 3 orbits. Battery cell balancing this orbit? Y	02/20/18	NGA
Balancing	 Verify charging cycle (Long eclipse flag=TRUE) is 90 minutes long. 	52,20,10	1.011
	FALSE.		
	4. Verify P/L is in HVSTANDBY or HVENG.		
	5. Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution.		
	6. Verify no charging cycle within 1 hour of maneuver.		
	7. Verify no charging cycle during an eclipse.		1

IBEX Command Approval Checklist	
C. Reno	

Cmd 1. Review CCVR. If you have any questions Reply All to the ATS Approval email and ask the team. Violation	02/20/18	NGA	
---	----------	-----	--

Activity	Anomaly Response : Non-nominal burn	Date Completed	Completed By
	 If the maneuver has not occurred or the spacecraft pointing as designated by either the star tracker or coarse Sun sensor is off by more than 2 degrees from the expected pointing, an anomaly has occurred. If the spacecraft is in Contingency state all stored commands are flushed from the command queue. Follow standard anomaly process. If the Sun maneuver did not occur and the spacecraft is in either Science or Housekeeping state follow the steps below. If a partial Sun maneuver has occurred and the spacecraft is in either Science or Housekeeping state follow the steps below. Please note that there is no anticipated hardware damage associated with exceeding the 12.5 degree constraint; this constraint is in place because we should not exceed the largest pointing achieved thus for in the mission. 		
	 far in the mission. If the payload is in HVSTANDBY, LVENG or OFF, and there are no commands loaded to bring it to HVSCI voltages, no operational pointing constraints will be violated. Follow standard anomaly process. If the payload in HVSCI mode or there are uploaded commands to bring the payload to HVSCI mode, a. Determine current off Sun pointing. If the off Sun angle has already exceeded 12.5 degrees, the MOC should notify the MOM and immediately send the DESCENDING command suite in real-time, as described below. If this cannot be done in the contact where the pointing anomaly was discovered, another contact will be planned as soon as possible to execute these commands. @CEU_MACRO_EXEC DESCENDING_PL1 (<1 min) @CEU_MACRO_EXEC DESCENDING_HI (<8 min) @CEU_MACRO_EXEC DESCENDING_PL2 (<1 min) @CEU_MACRO_EXEC DESCENDING_NO payload-specific action is needed for this arc. Follow standard anomaly response process. @		