IBEX Command Approval Checklist Rev 16e removes the Moon in Lo FOV section.

Orbit	449	Special Ops				
14 R _E asc. Date/Time	6/1/2019 10:	17:20	15 R _E asc. Date/Time	6/1/2019 12:2	0:24	
Apogee	6/5/2019 16:26:10	Maneuver Window Start	6/5/2019 06:26:25	Maneuver Window End	6/6/2019 02:26:27	
Apogee Target		05100000000000 27599999999999	2 targetY:0.87747)	7799999999998		
15 R _E desc. Date/Time	6/9/2019 19:	59:23	14 R _E desc. Date/Time	6/9/2019 21:59:03		
Perigee	6/10/2019 06:56:19	Maneuver Window Start	6/9/2019 22:29:31	Maneuver Window Stop	6/10/2019 15:53:54	
Perigee Target		78099999999999 66499999999999	0 targetY:0.89629	9999999999999		
Eclipse	No	Eclipse Start		Eclipse End		
Sun Mnvr	No	Apogee/Perigee		Sun Angle at DESCENDING		
Approved Version	IBEX_2019_152	_o0449a_v001.s	scr			

Activity	Command Checks	Date Done	Done By
Supporting Materials	 IBEX_CrossingTimes_<date>_v00x.txt on SFTP at /Archive-Incoming/IBEXIncoming/FDG/PredictedEphemeris/Orbit Events/.</date> Orbit Events File on SFTP at /IBEXOutgoing/MOC/Moc-Soc/oef/. Command Constraint Violations Report on SFTP at /IBEXOutgoing/MOC/Moc-Soc/cvr/. Contacts this orbit Orbit_oXXX.txt included in the ATS approval email. Science Tasking File at /Archive-Incoming/IBEXIncoming/MOC/Soc-Moc/stf/. Merged ATS at http://ibex.unh.edu/cgi-bin/ats.cgi. 	05/21/19	NGA
Sun Maneuvers	• Additional contacts <i>should not</i> be planned to support IBEX Sun Precession Maneuvers due to star tracker outages. The standard apogee and perigee contacts should be used to verify that a maneuver has occurred. If it is not possible to plan one of the standard contacts after the star tracker outage is down to 50% and a valid quaternion reading can be made to verify the maneuver, the coarse Sun sensor angle and the thruster pulse count will be used to determine a) whether a maneuver took place, and b) whether the pointing after the maneuver is as expected +/- 2 degrees.	N/A	NGA
	• The nominal off-Sun pointing constraint is 7.25 degrees. Based on the missed maneuver in orbit 114, the payload team has determined that there is no hardware risk associated with off-Sun pointing up to angles of at least 13 degrees. There is a higher background noted in the data starting at around 9.5 degrees off Sun pointing.		
File Input Check	 Current OEF inputs are Forecast STF, last orbit's OEF & latest predictive ephemeris. ATS inputs are this orbit's OEF & STF. (And ABS if present.) ATS filename is of the format IBEX_yyyy_doy_o0xxxa_v0zz.scr. where IBEX is capitalized, yyyy is the year, doy is the day of year, xxx is the 3-digit orbit number and zz is the 2-digit version number. Any special operations ATSs will have another designation between the orbit number and version number (i.e. *o0186a_hgc_v001 for the Hi gain curve). 	05/21/19	NGA

Eclipses	1.	Check OEF for eclipses during the orbit.	N/A	NGA
Luipses	2.	Verify long eclipse flag start & stop times reflect Ryan Tyler's recommendations based on his	IN/A	NGA
		eclipse diagnostic tool. Suggestions made by Ryan after the use of this tool trump the general		
		guidelines below. (Please note, specific timing may shift if the recommendations are relative to		
		eclipse timing. For example, it may say set LE flag to false X hours after the end of the eclipse		
		with a given FALSE time suggested. If the eclipse timing changes as the ephemeris becomes		
		more refined, this command time may shift.)		
	3.	Verify no contacts planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
		recommendations will trump the general guidelines below. a. Verify transmitter OFF from 30 minutes before eclipse start through the end of the		
		eclipse.		
		b. For an eclipse where the long eclipse flag is set, schedule a SOH contact directly		
		following the end of the eclipse (or per Ryan's assessment).		
		c. Set the LE flag according to Ryan's assessments.		
	4.	Verify no maneuver planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
		recommendations will trump the general guidelines below.		
		 Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through 3 hours after eclipse end. 		
		b. Verify no maneuver or cat bed heaters are on while the long eclipse flag is set.		
	5.	Verify the following additional constraints (from battery balancing section).		
		a. Verify the first command sets the long eclipse flag to TRUE, the second command sets		
		the flag to FALSE. b. Verify P/L is in HVSTANDBY or HVENG.		
		c. Verify P/L is in TrySTANDB1 of TVENG. c. Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro		
		execution.		
		This applies to all eclipses, not just moderate or long eclipses.		
Contact	1.	Verify STX on/off times, downlink rate against Orbit_oXXX.txt file.	05/21/19	NGA
Commands	2.	Verify contacts in the previous ATS have not been duplicated.	03/21/19	NGA
Communa	3.	Verify all currently planned contacts in Orbit_xxx.txt are in the ATS.		
	4.	Verify each contact contains the following 5 commands.		
		SetRelay stx,on		
		 SetDownlink2K (2K, 40K, 64K, 160K, or 320K) 		
		 SetBilevelOutputControlReg STXMODE_Strobe,ON 		
		SetBilevelOutputControlReg COHERENT,ON		
		SetRelay stx,off		
	5.	If contact is near an eclipse		
		Verify transmitter OFF from 30 minutes before eclipse start through 30 minutes after		
		eclipse end. b. If additional transmitter constraints exist, they will be captured in Ryan's		
		recommendations.		
	6.	If an APL contact is being used for an SSR Dump, the data rate should be at least 160 ksps & the		
		SSR DUMP_NEW command should be included in the contact commands. Commands in Orange		
		should only be sent if the SSR pointers need to be reset this perigee. These commands should		
		be separated by 2s and occur 2s after the SSR_DUMP_NEW command.		
		SetRelay stx,on SetRelay stx,on		
		SetDownlink2K SetBilayolOutputCentrolPeg STYMODE Strobe ON		
		SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg COHERENT ON		
		 SetBilevelOutputControlReg COHERENT,ON SetDownlink320K 		
		SER DUMP NEW		
		• SSR_DOWNP_NEW • SSR_SET_RD_PTR 6500		
		• SSR_SET_WRT_PTR 6500		
		SetRelay stx,off		
		- Settled Julyon		

SC State	1.	Transition to Science state will be first command of each ATS (at 14 Re).	05/21/19	NGA
Science:		• SetScState science \$TIME=2019/06:01:10:17:33		
arc a	2.	Lo science mode will be the next command (at 14 Re).		
		LO_SCIENCE_MODE NORMAL		
	3.	Verify no transition to Science again at the end of the ATS. The ATS commands go from 14 Re to		
		14 Re in each orbit.		
	4.	Verify the transition to Science commands for this orbit are not part of the previous ATS using		
		http://ibex.unh.edu/cgi-bin/ats.cgi.		
	5.	Verify that the beginning of this ATS does not overlap with the end of the previous orbit's ATS		
		using http://ibex.unh.edu/cgi-bin/ats.cgi.		
Payload	1.	Verify w/ Crossing Times report that it occurs about 15 Re ascending. The arc a ASCENDING	05/21/19	NGA
Mode	_	commands can start any time at or above 15 Re ascending.		
HVSCI:	2.	Verify commanding takes ~ 24 minutes.		
arc a		• ASCENDING_PL1 \$TIME=2019/06:01:12:20:32		
		ASCENDING_HI SET_PARAMETER 1_TIME_PATE_SOLUTION		
		SET_PARAMETER 1, TLM_RATE_SOH SET_PARAMETER 1, TLM_CATER_SOH		
		SET_PARAMETER 4, HV_STEP_DWELL SET_PARAMETER 3, HV_STEP_FRAG		
		SET_PARAMETER 3, HV_STEP_FRAC HILLORD AND ADDRESS AND ADD		
		HI_COL_NEG_LVL 1400		
		CEU_HI_CEM_1_LVL 1780 CEV_HI_CEM_1_LVL 1780		
		CEU_HI_CEM_2_LVL 1780 CEU_HI_CEM_2_LVL 1780		
		CEU_HI_CEM_3_LVL 1780		
		CEU_HI_CEM_4_LVL 1900		
		SET_PARAMETER 0, TLM_RATE_SOH		
		ASCENDING_PL2		
		ASCENDING_PL1		
		ASCENDING_LO		
		• ASCENDING_PL2 \$TIME=2019/06:01:12:44:20		
Payload	1.	Payload DESCENDING commands end 1.5h before thruster enable.	05/21/19	NGA
Mode	2.	Verify commands take ~23 minutes to execute.	00/21/10	110,1
HVSTANDBY		• DESCENDING_PL1 \$TIME=2019/06:05:04:30:27		
: arc a		DESCENDING_LO		
		ASCENDING_PL2		
		• DESCENDING_PL1		
		DESCENDING_HI		
		• DESCENDING_PL2 \$TIME=2019/06:05:04:53:17		
SC State	1.	Spacecraft Housekeeping command occurs 1h before thruster enable.	05/21/19	NGA
HK : arc a		SetScState housekeeping \$TIME=2019/06:05:05:26:27	20,2.,.0	

Inertial Maneuver: Apogee Apogee 2. Verify Thruster enable command occurs within STF maneuver window. 3. Verify no eclipse occurs from cat bed heater on through set FC mode Mission. 4. Verify cat bed heaters come on 55 min before burn. • CATBED_5N_HTR,ON \$TIME=2019/06:05:05:31:25 5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. • SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999	1113	NGA
2. Verify Thruster enable command occurs within STF maneuver window. 3. Verify no eclipse occurs from cat bed heater on through set FC mode Mission. 4. Verify cat bed heaters come on 55 min before burn. • CATBED_5N_HTR,ON \$TIME=2019/06:05:05:31:25 5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. • SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999		
 Verify no eclipse occurs from cat bed neater on through set FC mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON \$TIME=2019/06:05:05:31:25 Verify Kalman Filter input select is ground command & estimator update is disabled. SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE Verify in FC mode Burn. SetFcMode burn Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999		
 CATBED_5N_HTR,ON \$TIME=2019/06:05:05:31:25 Verify Kalman Filter input select is ground command & estimator update is disabled. SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE Verify in FC mode Burn. SetFcMode burn Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999		
 5. Verify Kalman Filter input select is ground command & estimator update is disabled. SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999		
 SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276		
 SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX: 0.30605100000000002 targetY: 0.877477999999999999999999999999999999999		
 6. Verify in FC mode Burn. SetFcMode burn 7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX: 0.306051000000000002 targetY: 0.877477999999999999999999999999999999999		
 SetFcMode burn Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. SetInrDir 0.306051,0.877478,0.369276 targetX:0.30605100000000002 targetY:0.877477999999999999999999999999999999999		
7. Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match. • SetInrDir 0.306051,0.877478,0.369276 targetX: 0.30605100000000002 targetY: 0.877477999999999999999999999999999999999		
match. • SetInrDir 0.306051,0.877478,0.369276 targetX:0.30605100000000002 targetY:0.877477999999999999999999999999999999999		
targetX:0.30605100000000002 targetY:0.87747799999999998 targetZ:0.3692759999999999		
targetZ:0.369275999999999		
8. Verify inertial maneuver chosen.		
SetLrTarget ACS_INERTIAL		
9. Verify thrust time set to 11 min.		
SetThrustTime 660		
10. Verify thruster enable command matches RepointingManeuverStart time in OEF.		
SetThrustEnable ENABLE \$TIME=2019/06:05:06:26:25		
RepointingManeuverStart 2019-06-05T06:26:25		
11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
to 0.		
SetUTPCond CATRED EN LUTP OFF		
SetHTRCmd CATBED_5N_HTR,OFF SetThrustTime 0		
12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:05:06:51:35		
SetStaticZrate ESTIMATOR, 0.416 \$TIME=2019/06.05.06.51.55 SetKFInputSelect STA_PCT_VALID, 43,28,33,48		
Settrinpuselect STA_PCI_VALID, 43,28,33,48 SetFcMode Mission		
1. He this command convence in the event of an energy Cun managery		
Sun 1. Use this command sequence in the event of an apogee Sun maneuver. N/ Precession 2. Verify Thruster enable command occurs within STF maneuver window.	Α	NGA
Verify no political and had been an through act TC made Mission		
: Apogee 4. Verify cat bed heaters powered on 55 min before thruster enable.		
• CATBED_5N_HTR,ON		
5. Verify in FC mode Burn and Sun target.		
SetFcMode burn		
SetLrTarget ACS_SUN		
6. Verify thrust time set to 16 min.		
SetThrustTime 960 Verify the material and the common directable a SymMirr Degrin time in OFF.		
7. Verify thruster enable command matches SunMvrBegin time in OEF.		
SetThrustEnable ENABLE SunMarRania		
SunMvrBegin Verify 15 minutes offer the vertex and head and head and head are off the vertex and head are offer the v		
8. Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. FC mode Mission.		
SetThrustEnable DISABLE		
SetHTRCmd CATBED_5N_HTR,OFF SetThrustTime 0		
SetTrustTime 0 SetFcMode Mission		
	\longrightarrow	
SC State Sc State Sc State SetScState science \$TIME=2019/06:05:07:41:31	1/19	NGA
Science:		
arc b LO_SCIENCE_MODE NORMAL		

Payload Mode HVSCI: arc b	1. Verify payload ASCENDING commands begin at least 1.5 hours after thruster DISABLE. 2. Verify commands take ~24 minutes to execute. • ASCENDING_PL1 \$TIME=2019/06:05:08:11:31 • ASCENDING_HI • SET_PARAMETER 1, TLM_RATE_SOH • SET_PARAMETER 4, HV_STEP_DWELL • SET_PARAMETER 3, HV_STEP_FRAC • HI_COL_NEG_LVL 1400 • CEU_HI_CEM_1_LVL 1780 • CEU_HI_CEM_2_LVL 1780 • CEU_HI_CEM_3_LVL 1780 • CEU_HI_CEM_3_LVL 1780 • CEU_HI_CEM_4_LVL 1900 • SET_PARAMETER 0, TLM_RATE_SOH • ASCENDING_PL2 • ASCENDING_PL1 • ASCENDING_DL0 • ASCENDING_D PL2 \$TIME=2019/06:05:08:35:19	05/21/19	NGA
Payload Mode HVSTANDBY : arc b	1. Verify w/ Crossing Times report that it occurs about 15 Re descending. The arc b DESCENDING commands can complete any time at or above 15 Re descending. 2. Verify commands take ~23 minutes to execute. • DESCENDING_PL1 \$TIME=2019/06:09:19:33:20 • DESCENDING_LO • ASCENDING_PL2 • DESCENDING_PL1 • DESCENDING_PL1 • DESCENDING_HI • DESCENDING_PL2 \$TIME=2019/06:09:19:56:10	05/21/19	NGA
SC State HK : arc b	Verify with Crossing Times report that Transition to Housekeeping state occurs at 14 Re desc (or an hour before the maneuver if the maneuver occurs less than 1 hour after 14 Re desc). SetScState housekeeping \$TIME=2019/06:09:21:29:05	05/21/19	NGA

Maneuver: Perigee Precession Maneuver: Perigee' sequence below. Verify no eclipse occurs from cat bed heater on through set FC mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON \$TIME=2019/06:09:21:34:31 Verify in Housekeeping state. Verify Kalman Filter input select is ground command & estimator update is disabled. **SettShiputSelect GND_CMD, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE Verify in FC mode Burn. **SetFcMode burn Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. **SetInrDir 0.230781,0.8963,0.378665 targetX: 0.23078099999999999999999999999999999999999	NGA
Perigee 2. Verify no eclipse occurs from cat bed heater on through set FC mode Mission. 3. Verify cat bed heaters come on 55 min before burn. • CATBED_SN_HTR,ON STIME=2019/06:09:21:34:31 4. Verify in Housekeeping state. 5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetPCMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir 0.230781,0.8963,0.378665 targetX: 0.23078099999999999999999999999999999999999	
3. Verify cat bed heaters come on 55 min before burn. • CATBED_SN_HTR,ON_STIME=2019/06:09:21:34:31 4. Verify in Housekeeping state. 5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir 0.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
CATBED_5N_HTR,ON \$TIME=2019/06:09:21:34:31 4. Verify in Housekeeping state. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir in O.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
4. Verify in Housekeeping state. 5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SetKFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir 0.230781,0.8963,0.378665 targetX: 0.23078099999999999999999999999999999999999	
5. Verify Kalman Filter input select is ground command & estimator update is disabled. • SettFInputSelect GND_CMD, 0, 0, 0, 0 • SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir 0.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
 SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetEstUpdateEnables ENABLE, DISABLE 6. Verify in FC mode Burn. SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. SetInrDir 0.230781,0.8963,0.378665	
SetEstUpdateEnables ENABLE, DISABLE Verify in FC mode Burn. SetFcMode burn Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. SetInrDir 0.230781,0.8963,0.378665 targetX: 0.23078099999999999999999999999999999999999	
6. Verify in FC mode Burn. • SetFcMode burn 7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. • SetInrDir 0.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
SetFcMode burn Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. SetInrDir 0.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
7. Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. SetInrDir 0.230781,0.8963,0.378665 targetX:0.23078099999999999999999999999999999999999	
 SetInrDir 0.230781,0.8963,0.378665 targetX: 0.23078099999999999999999999999999999999999	
targetX:0.23078099999999999999999999999999999999999	
targetZ:0.37866499999999999999999999999999999999999	
targetZ:0.37866499999999999999999999999999999999999	
8. Verify inertial maneuver chosen. SetLrTarget ACS_INERTIAL 9. Verify thrust time set to 11 min. SetThrustTime 660 10. Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48	
 SetLrarget ACS_INERTIAL Verify thrust time set to 11 min. SetThrustTime 660 Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
9. Verify thrust time set to 11 min. SetThrustTime 660 10. Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48	
 SetThrustTime 660 10. Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 10. Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 SetThrustEnable ENABLE \$TIME=2019/06:09:22:29:31 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 RepointingManeuverStart 2019-06-09T22:29:31 11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
11. Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0. • SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 • CATBED_5N_HTR,OFF • SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. • SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 • SetKFInputSelect STA_PCT_VALID, 43,28,33,48	
to 0. SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48	
 SetThrustEnable DISABLE \$TIME=2019/06:09:22:39:31 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 CATBED_5N_HTR,OFF SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 SetThrustTime 0 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 12. Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
 SetStaticZrate ESTIMATOR, 0.418 \$TIME=2019/06:09:22:54:41 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 	
SetKFInputSelect STA_PCT_VALID, 43,28,33,48	
0 15 24 1 24: 1	
SetFcMode Mission	
Sun 1. Use this command sequence in the event of a perigee Sun maneuver.	NGA
Precession 2. Verify Thruster enable command occurs within STF maneuver window.	NGA
Maneuver: 3. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission.	
Perigee 4. Verify cat bed heaters come on 55 min before burn.	
CATBED_5N_HTR,ON	
5. Verify in FC mode Burn and Sun target.	
SetFcMode burn	
SetLrTarget ACS_SUN	
6. Verify thrust time set to 16 min.	
SetThrustTime 960	
7. Verify thruster enable command matches SunMvrBegin time in OEF.	
SetThrustEnable ENABLE	
SunMvrBegin	
8. Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set	
to 0, FC mode Mission.	
SetThrustEnable DISABLE	
SetHTRCmd CATBED_5N_HTR,OFF	
 SetThrustTime 0 SetFcMode Mission 	

IBEX Command Approval Checklist K. Fairchild

				Rev	16e
Last up	date	09/1	2/20	18	

Battery Cell Balancing	1. 2. 3. 4. 5. 6. 7.	There will be battery cell balancing every 2 out of 3 orbits. Battery cell balancing this orbit? N Verify charging cycle (Long eclipse flag=TRUE) is 90 minutes long. Verify the first command sets the long eclipse flag to TRUE, the second command sets the flag to FALSE. Verify P/L is in HVSTANDBY or HVENG. Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution. Verify no charging cycle within 1 hour of maneuver. Verify no charging cycle during an eclipse.	05/21/19	NGA
Cmd Violation	1.	Review CCVR. If you have any questions Reply All to the ATS Approval email and ask the team.	05/21/19	NGA

Activity		Anomaly Response : Non-nominal burn	Date Completed	Completed By
	•	If the maneuver has not occurred or the spacecraft pointing as designated by either the star tracker or coarse Sun sensor is off by more than 2 degrees from the expected pointing, an anomaly has occurred.		
		If the spacecraft is in Contingency state all stored commands are flushed from the command queue. Follow standard anomaly process. **Title On the Command of the Comm		
		If the Sun maneuver did not occur and the spacecraft is in either Science or Housekeeping state follow the steps below. (1)		
		 If a partial Sun maneuver has occurred and the spacecraft is in either Science or Housekeeping state follow the steps below. 		
	•	Please note that there is no anticipated hardware damage associated with exceeding the 12.5 degree constraint; this constraint is in place because we should not exceed the largest pointing achieved thus far in the mission.		
	1.	If the payload is in HVSTANDBY, LVENG or OFF, and there are no commands loaded to bring it to HVSCI voltages, no operational pointing constraints will be violated. Follow standard anomaly process.		
	2.	If the payload is in HVSCI mode or there are uploaded commands to bring the payload to HVSCI mode,		
		 a. Determine current off Sun pointing. If the off Sun angle has already exceeded 12.5 degrees, the MOC should notify the MOM and immediately send the DESCENDING command suite in real-time, as described below. If this cannot be done in the contact where the pointing anomaly was discovered, another contact will be planned as soon as possible to execute these commands. @CEU_MACRO_EXEC_DESCENDING_PL1 (< 1 min) 		
		<pre>@CEU_MACRO_EXEC DESCENDING_LO (~ 10 min) @CEU_MACRO_EXEC DESCENDING_HI (~ 8 min) @CEU_MACRO_EXEC DESCENDING_PL2 (< 1 min) Please note: The only scenario where hitting 12.5 degrees is expected is when a</pre>		
		perigee Sun precession maneuver is completely missed after an inertial apogee maneuver which occurs late in the maneuver window (near apogee + 10 hours). b. If current Sun pointing is below 12.5 degrees, the ISOC should input ST Sun-		
		pointing angle into ibex_rotate to determine the Sun angle at the time of DESCENDING. Sun-Angle at payload DESCENDING		
		c. If 12.5 degrees is not exceeded by the time of DESCENDING, no payload-specific action is needed for this arc. Follow standard anomaly response process.		
		 If 12.5 degrees is exceeded by the time of DESCENDING, a new command set should be sent. 		
		 The ISOC will generate the new STF which has the DESCENDING commands executing early such that 12.5 degrees is not exceeded while the payload is in HVSCI. 		
		 ii. The MOC will create an associated ATS. iii. Approval is needed by the MOM, MOC & ISOC prior to upload. iv. The MOC will assess whether an additional pass is needed in order to upload the commands prior to exceeding the 12.5 degree constraint. The 		
		onboard DESCENDING commands do not need to be deleted.		