IBEX Command Approval Checklist Rev 16g changes SSR pointer reset values; adds a clarification

Orbit	507	Special Ops				
14 R _E asc. Date/Time	11/10/2020 0	0:57:56	15 R _E asc. Date/Time	- I		
Apogee	11/14/2020 06:26:47	Maneuver Window Start	11/13/2020 20:26:49	Maneuver Window End	11/14/2020 16:26:51	
Apogee Target	<pre>targetX:-0.64760300000000004 targetY:-0.69505300000000003 targetZ:-0.312269000000002</pre>					
15 R _E desc. Date/Time	11/18/2020 0	20 07:06:31 14 R_E desc.				
Perigee	11/18/2020 17:20:32	Maneuver Window Start	11/18/2020 09:59:23	Maneuver Window Stop	11/19/2020 01:11:49	
Perigee Target	targetX:-0.5870400000000001 targetY:-0.7391480000000003 targetZ:-0.3302180000000001					
Eclipse	No	Eclipse Start		Eclipse End		
Sun Mnvr	No	Apogee/Perigee		Sun Angle at DESCENDING		
Approved Version	IBEX_2020_314_00507a_BUS_v001.scr, IBEX_2020_314_00507a_INST_v001.scr					

Activity		Command Checks	Date Done	Done By
Supporting Materials	1. 2. 3. 4. 5. 6.	IBEX_CrossingTimes_ <date>_v00x.txt on SFTP at /Archive-Incoming/IBEXIncoming/FDG/PredictedEphemeris/Orbit Events/. Orbit Events File on SFTP at /IBEXOutgoing/MOC/Moc-Soc/oef/. Command Constraint Violations Report on SFTP at /IBEXOutgoing/MOC/Moc-Soc/cvr/. Contacts this orbit Orbit_oXXX.txt included in the ATS approval email. Science Tasking File at /Archive-Incoming/IBEXIncoming/MOC/Soc-Moc/stf/. Merged ATS at http://ibex.unh.edu/cgi-bin/ats.cgi.</date>	10/26/20	NGA
Sun Maneuvers	•	Additional contacts <i>should not</i> be planned to support IBEX Sun Precession Maneuvers due to star tracker outages. The standard apogee and perigee contacts should be used to verify that a maneuver has occurred. If it is not possible to plan one of the standard contacts after the star tracker outage is down to 50% and a valid quaternion reading can be made to verify the maneuver, the coarse Sun sensor angle and the thruster pulse count will be used to determine a) whether a maneuver took place, and b) whether the pointing after the maneuver is as expected +/- 2 degrees.	N/A	NGA
	•	The nominal off-Sun pointing constraint is 7.25 degrees. Based on the missed maneuver in orbit 114, the payload team has determined that there is no hardware risk associated with off-Sun pointing up to angles of at least 13 degrees. There is a higher background noted in the data starting at around 9.5 degrees off Sun pointing.		
File Input Check	1. 2. 3.	Current OEF inputs are Forecast STF, last orbit's OEF & latest predictive ephemeris. ATS inputs are this orbit's OEF & STF. (And ABS if present.) ATS filename is of the format IBEX_yyyy_doy_o0xxxa_v0zz.scr. where IBEX is capitalized, yyyy is the year, doy is the day of year, xxx is the 3-digit orbit number and zz is the 2-digit version number. Any special operations ATSs will have another designation between the orbit number and version number (i.e. *o0186a hgc v001 for the Hi gain curve).	10/26/20 BUS & INST ATS split, so different input files	NGA

				1
Eclipses	1.	Check OEF for eclipses during the orbit.	N/A	
	2.	Verify long eclipse flag start & stop times reflect Ryan Tyler's recommendations based on his		
		eclipse diagnostic tool. Suggestions made by Ryan after the use of this tool trump the general		
		guidelines below. (Please note, specific timing may shift if the recommendations are relative to		
		eclipse timing. For example, it may say set LE flag to false X hours after the end of the eclipse		
		with a given FALSE time suggested. If the eclipse timing changes as the ephemeris becomes		
	3.	more refined, this command time may shift.) Verify no contacts planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
	3.	recommendations will trump the general guidelines below.		
		a Verify transmitter OFF from 30 minutes before eclipse start through the end of the eclipse.		
		b For an eclipse where the long eclipse flag is set, schedule a SOH contact directly		
		following the end of the eclipse (or per Ryan's assessment).		
		c Set the LE flag according to Ryan's assessments.		
	4.	Verify no maneuver planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
		recommendations will trump the general guidelines below.		
		 a Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through 3 hours after eclipse end. 		
		b Verify no maneuver or cat bed heaters are on while the long eclipse flag is set.		
	5.	Verify the following additional constraints (from battery balancing section).		
		a Verify the first command sets the long eclipse flag to TRUE, the second command		
		sets the flag to FALSE.		
		b Verify P/L is in HVSTANDBY or HVENG.		
		c Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro		
		execution.		
		This applies to all eclipses, not just moderate or long eclipses.		
Contact	1.	Verify STX on/off times, downlink rate against Orbit_oXXX.txt file.	10/26/20	NGA
Commands	2.	Verify contacts in the previous ATS have not been duplicated.	10/20/20	NOA
Communa	3.	Verify all currently planned contacts in Orbit_xxx.txt are in the ATS.		
	4.	Verify each contact contains the following 5 commands.		
		SetRelay stx,on		
		• SetDownlink2K (2K, 40K, 64K, 160K, or 320K)		
		SetBilevelOutputControlReg STXMODE_Strobe,ON		
		SetBilevelOutputControlReg COHERENT,ON		
		SetRelay stx,off		
	5.	If contact is near an eclipse		
		a. Verify transmitter OFF from 30 minutes before eclipse start through 30 minutes after eclipse		
		end.		
		b. If additional transmitter constraints exist, they will be captured in Ryan's recommendations.		
	6.	If an APL contact is being used for an SSR Dump, the data rate should be at least 160 ksps & the SSR DUMP_NEW command should be included in the contact commands. Commands in Orange should only		
		be sent if the SSR pointers need to be reset this perigee. These commands should be separated by 2s and		
		occur 2s after the SSR_DUMP_NEW command.		
		SetRelay stx,on		
		SetDownlink2K		
		 SetBilevelOutputControlReg STXMODE_Strobe,ON 		
		SetBilevelOutputControlReg COHERENT,ON		
]
		SetDownlink320K		
		SetDownink320k SSR_DUMP_NEW		
		• SSR_DUMP_NEW		

				1
SC State	1.	Transition to Science state will be first command of each ATS (at 14 Re).	10/26/20	NGA
Science:		• SetScState science \$TIME=2020/11:10:00:58:45		
arc a	2.	Lo science mode will be the next command (at 14 Re).		
		LO_SCIENCE_MODE NORMAL		
	3.	Verify no transition to Science again at the end of the ATS. The ATS commands go from 14 Re to 15 Re in each orbit.		
	4.	Verify the transition to Science commands for this orbit are not part of the previous ATS using		
		http://ibex.unh.edu/cgi-bin/ats.cgi.		
	5.	Verify that the beginning of this ATS does not overlap with the end of the previous orbit's ATS		
		using http://ibex.unh.edu/cgi-bin/ats.cgi.		
Payload Mode	1.	Verify w/ Crossing Times report that it occurs about 15 Re ascending. The arc a ASCENDING commands can start any time at or above 15 Re ascending.	10/26/20	NGA
HVSCI:	2.	Verify commanding takes ~ 24 minutes.		
arc a		ASCENDING_PL1 \$TIME=2020/11:10:03:48:13		
		ASCENDING HI		
		SET_PARAMETER 1, TLM_RATE_SOH		
		SET_PARAMETER 4, HV_STEP_DWELL		
		SET_PARAMETER 3, HV_STEP_FRAC		
		HI COL NEG LVL 1400		
		• CEU_HI_CEM_1_LVL 1780		
		• CEU_HI_CEM_2_LVL 1780		
		• CEU_HI_CEM_3_LVL 1780		
		• CEU_HI_CEM_4_LVL 1900		
		SET_PARAMETER 0, TLM_RATE_SOH		
		ASCENDING PL2		
		ASCENDING_PL1		
		ASCENDING LO		
		• ASCENDING_PL2 \$TIME=2020/11:10:04:12:01		
D!			40/00/00	NCA
Payload		Payload DESCENDING commands end 1.5h before thruster enable.	10/26/20	NGA
Mode HVSTANDBY	2.	Verify commands take ~23 minutes to execute.		
: arc a		• DESCENDING_PL1 \$TIME=2020/11:13:18:30:51		
. 0.0 0		DESCENDING_LO		
		ASCENDING_PL2		
		DESCENDING_PL1		
		• DESCENDING_HI		
		• DESCENDING_PL2 \$TIME=2020/11:13:18:53:41		
SC State	1.	Spacecraft Housekeeping command occurs 1h before thruster enable.	10/26/20	NGA
HK : arc a		 SetScState housekeeping \$TIME=2020/11:13:19:26:51 	10/20/20	NOA
, u	1	2010001010 2010 Coping 911111 2020/11110110101		1

IBEX Command Approval Checklist K. Fairchild

Γ			1	ı
Inertial	1.	Use this command sequence if an apogee inertial maneuver is used, otherwise skip to the 'Sun	10/26/20	NGA
Maneuver:	١,	Precession Maneuver : Apogee' sequence below. Verify Thruster enable command occurs within STF maneuver window.		
Apogee	2. 3.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission.		
		Verify cat bed heaters come on 55 min before burn.		
	٦.	CATBED_5N_HTR,ON \$TIME=2020/11:13:19:31:49		
	5.	Verify Kalman Filter input select is ground command & estimator update is disabled.		
	٦.			
		SetKFInputSelect GND_CMD, 0, 0, 0, 0 SetFetUndeteFachler FNARIF FNARIF		
	_	SetEstUpdateEnables ENABLE, DISABLE Variety in EC manda Pure.		
	6.	Verify in FC mode Burn.		
	_	SetFcMode burn Company Catlor Diving ATC with pointing and defined in the Foregoet STE 8 world, the western		
	7.	Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match.		
		• SetInrDir -0.647603,-0.695053,-0.312269		
		targetX:-0.64760300000000004 targetY:-0.6950530000000003		
		targetZ:-0.3122690000000002		
	8.	Verify inertial maneuver chosen.		
		SetLrTarget ACS_INERTIAL Variety the model from a set to 4.4 miles		
	9.	Verify thrust time set to 11 min.		
	10	SetThrustTime 660 Verify thruster enable command metaboo RenaintingManage erset time in OFF		
	10.	Verify thruster enable command matches RepointingManeuverStart time in OEF.		
		SetThrustEnable ENABLE \$TIME=2020/11:13:20:26:49		
		RepointingManeuverStart 2020/11:13:20:26:49 Verify 10 print to a first black and the start and		
	11.	Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0.		
		SetThrustEnable DISABLE \$TIME=2020/11:13:20:36:49		
		SetHTRCmd CATBED_5N_HTR,OFF		
		SetThrustTime 0		
	12.	Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
		SetStaticZrate ESTIMATOR, 0.418 \$TIME=2020/11:04:19:06:34		
		 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 		
		SetFcMode Mission		
Sun	1.	Use this command sequence in the event of an apogee Sun maneuver.	N/A	
Precession	2.	Verify Thruster enable command occurs within STF maneuver window.		
Maneuver	3.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission.		
: Apogee	4.	Verify cat bed heaters powered on 55 min before thruster enable.		
		• CATBED_5N_HTR,ON		
	5.	Verify in FC mode Burn and Sun target.		
		SetFcMode burn		
		SetLrTarget ACS_SUN Variety than 14 times and 14 AC main.		
	6.	Verify thrust time set to 16 min.		
	_	SetThrustTime 960 A B i ii i OFF		
	7.	Verify thruster enable command matches SunMvrBegin time in OEF.		
		SetThrustEnable ENABLE		
		SunMvrBegin		
	8.	Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0, FC mode Mission.		
		SetThrustEnable DISABLE SetUTECON CATEGORIES		
		SetHTRCmd CATBED_5N_HTR,OFF		
		SetThrustTime 0		
		SetFcMode Mission		
		0 00 1 4 6 0 1 0 1	1	ı
SC State	1.	Spacecraft Science commands occur ~1h after thruster Disable.	10/26/20	NGA
SC State Science :	1.	 Spacecraft Science commands occur ~1n after thruster Disable. SetScState science \$TIME=2020/11:13:21:41:55 LO_SCIENCE_MODE NORMAL 	10/26/20	NGA

Payload Mode HVSCI : arc b	1. Verify payload ASCENDING commands begin at least 1.5 hours after thruster DISABLE. 2. Verify commands take ~24 minutes to execute. • ASCENDING_PL1 \$TIME=2020/11:13:22:11:55 • ASCENDING_HI • SET_PARAMETER 1, TLM_RATE_SOH • SET_PARAMETER 4, HV_STEP_DWELL • SET_PARAMETER 3, HV_STEP_FRAC • HI_COL_NEG_LVL 1400 • CEU_HI_CEM_1_LVL 1780 • CEU_HI_CEM_2_LVL 1780 • CEU_HI_CEM_3_LVL 1780 • CEU_HI_CEM_4_LVL 1900 • SET_PARAMETER 0, TLM_RATE_SOH • ASCENDING_PL2 • ASCENDING_PL1 • ASCENDING_LO • ASCENDING_LO	10/26/20	NGA
Payload Mode HVSTANDBY : arc b	 Verify W/ Crossing Times report that it occurs about 15 Re descending. The arc b DESCENDING commands can complete any time at or above 15 Re descending. Verify commands take ~23 minutes to execute. DESCENDING_PL1 \$TIME=2020/11:18:06:40:33 DESCENDING_LO ASCENDING_PL2 DESCENDING_PL1 DESCENDING_PL1 DESCENDING_PL1 DESCENDING_HI DESCENDING_PL2 \$TIME=2020/11:18:07:03:23 	10/26/20	NGA
SC State HK : arc b	 Verify with Crossing Times report that Transition to Housekeeping state occurs at 14 Re desc (or an hour before the maneuver if the maneuver occurs less than 1 hour after 14 Re desc). SetScState housekeeping \$TIME=2020/11:18:08:59:23 	10/26/20	NGA

Inertial	1.	Use this command sequence if a perigee inertial maneuver is used, otherwise skip to the 'Sun	10/26/20	NGA
Maneuver:		Precession Maneuver: Perigee' sequence below.		
Perigee	2. 3.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission. Verify cat bed heaters come on 55 min before burn.		
	э.	CATBED_5N_HTR,ON \$TIME=2020/11:18:09:04:23		
	4.	Verify in Housekeeping state.		
	5.	Verify Kalman Filter input select is ground command & estimator update is disabled.		
	٥.	SetKFInputSelect GND_CMD, 0, 0, 0, 0		
		SetEstUpdateEnables ENABLE, DISABLE		
	6.	Verify in FC mode Burn.		
	0.	SetFcMode burn		
	7.	Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match.		
	/٠	SetInrDir -0.58704,-0.739148,-0.330218		
		targetX:-0.5870400000000001 targetY:-0.7391480000000003		
		targetZ:-0.3302180000000001		
	8.	Verify inertial maneuver chosen.		
	0.	SetLrTarget ACS_INERTIAL		
	9.	Verify thrust time set to 11 min.		
	٥.	SetThrustTime 660		
	10.	Verify thruster enable command matches RepointingManeuverStart time in OEF.		
		SetThrustEnable ENABLE \$TIME=2020/11:18:09:59:23		
		RepointingManeuverStart 2020-11-18T09:59:23		
	11.	Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0.		
		 SetThrustEnable DISABLE \$TIME=2020/11:18:10:09:23 		
		• CATBED 5N HTR,OFF		
		SetThrustTime 0		
	12.	Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
		 SetStaticZrate ESTIMATOR, 0.418 \$TIME=2020/11:18:10:24:33 		
		 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 		
		SetFcMode Mission		
_	1.	Use this command sequence in the event of a perigee Sun maneuver.		
Sun	2.	Verify Thruster enable command occurs within STF maneuver window.	N/A	
Precession		Verify no eclipse occurs from cat bed heater on through set FC Mode Mission.		
Maneuver :	4.	Verify cat bed heaters come on 55 min before burn.		
Perigee		• CATBED_5N_HTR,ON		
	5.	Verify in FC mode Burn and Sun target.		
		SetFcMode burn		
		SetLrTarget ACS_SUN		
	6.	Verify thrust time set to 16 min.		
		SetThrustTime 960		
	7.	Verify thruster enable command matches SunMvrBegin time in OEF.		
		SetThrustEnable ENABLE		
		SunMvrBegin		
	8.	Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0, FC mode Mission.		
		SetThrustEnable DISABLE		
		SetHTRCmd CATBED_5N_HTR,OFF		
		SetThrustTime 0		
<u> </u>		SetFcMode Mission		

IBEX Command Approval Checklist K. Fairchild

	Rev	16g
Last update 10/26/202	20	

Battery Cell Balancing	1. 2. 3. 4. 5. 6. 7.	There will be battery cell balancing every 2 out of 3 orbits. Battery cell balancing this orbit? Y Verify charging cycle (Long eclipse flag=TRUE) is 90 minutes long. Verify the first command sets the long eclipse flag to TRUE, the second command sets the flag to FALSE. Verify P/L is in HVSTANDBY or HVENG. (The DESCENDING_PL1 macro leaves us in HVENG; the DESCENDING_PL2 macro leaves us in HVSTANDBY.) Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution. Verify no charging cycle within 1 hour of maneuver. Verify no charging cycle during an eclipse.	10/26/20	NGA
Cmd Violation	1.	Review CCVR. If you have any questions Reply All to the ATS Approval email and ask the team.	10/26/20	NGA

Activity	Anomaly Response : Non-nominal burn	Date Completed	Completed By
	 If the maneuver has not occurred or the spacecraft pointing as designated by either the star tracker or coarse Sun sensor is off by more than 2 degrees from the expected pointing, an anomaly has occurred. If the spacecraft is in Contingency state all stored commands are flushed from the command queue. Follow standard anomaly process. If the Sun maneuver did not occur and the spacecraft is in either Science or Housekeeping state follow the steps below. 		
	 If a partial Sun maneuver has occurred and the spacecraft is in either Science or Housekeeping state follow the steps below. Please note that there is no anticipated hardware damage associated with exceeding the 		
	12.5 degree constraint; this constraint is in place because we should not exceed the largest pointing achieved thus far in the mission.		
	 If the payload is in HVSTANDBY, LVENG or OFF, and there are no commands loaded to bring it to HVSCI voltages, no operational pointing constraints will be violated. Follow standard anomaly process. If the payload is in HVSCI mode or there are uploaded commands to bring the payload to 		
	2. If the payload is in HVSCI mode of there are uploaded commands to bring the payload to HVSCI mode, a. Determine current off Sun pointing. If the off Sun angle has already exceeded 12.5 degrees, the MOC should notify the MOM and immediately send the DESCENDING command suite in real-time, as described below. If this cannot be done in the contact where the pointing anomaly was discovered, another contact will be planned as soon as possible to execute these commands. @CEU_MACRO_EXEC DESCENDING_PL1 (< 1 min) @CEU_MACRO_EXEC DESCENDING_LO (~ 10 min) @CEU_MACRO_EXEC DESCENDING_HI (~ 8 min) @CEU_MACRO_EXEC DESCENDING_PL2 (< 1 min) Please note: The only scenario where hitting 12.5 degrees is expected is when a perigee Sun precession maneuver is completely missed after an inertial apogee maneuver which occurs late in the maneuver window (near apogee + 10 hours). b. If current Sun pointing is below 12.5 degrees, the ISOC should input ST Sunpointing angle into ibex_rotate to determine the Sun angle at the time of DESCENDING. Sun-Angle at payload DESCENDING c. If 12.5 degrees is not exceeded by the time of DESCENDING, no payload-specific action is needed for this arc. Follow standard anomaly response process.		
	 d. If 12.5 degrees is exceeded by the time of DESCENDING, a new command set should be sent. i. The ISOC will generate the new STF which has the DESCENDING commands executing early such that 12.5 degrees is not exceeded while the payload is in HVSCI. ii. The MOC will create an associated ATS. iii. Approval is needed by the MOM, MOC & ISOC prior to upload. iv.The MOC will assess whether an additional pass is needed in order to upload the commands prior to exceeding the 12.5 degree constraint. The onboard DESCENDING commands do not need to be deleted. 		