IBEX Command Approval Checklist

Rev 16h reduces battery cell balancing offset from maneuvers					
Orbit	617	Special Ops			
14 R _E asc. Date/Time	8/7/2023 11:3	32:40	15 R _E asc. Date/Time	8/7/2023 13:2	7:36
Apogee	8/11/2023 15:38:59	Maneuver Window Start	8/11/2023 05:43:03	Maneuver Window End	8/12/2023 01:43:05
Apogee Target	<pre>targetX:-0.719 targetZ:0.2670</pre>		06 targetY:0.6409	91699999999996	
15 R _E desc. Date/Time	8/15/2023 18	:30:20	14 R _E desc. Date/Time	8/15/2023 20:30:05	
Perigee	8/16/2023 05:27:18	Maneuver Window Start	8/15/2023 21:04:05	Maneuver Window Stop	8/16/2023 14:28:57
Perigee Target	targetX:-0.770 targetZ:0.2450		99 targetY:0.5879	94000000000002	
Eclipse	No	Eclipse Start		Eclipse End	
Sun Mnvr	No	Apogee/Perigee		Sun Angle at DESCENDING	
Approved Version	IBEX_2023_219	_00617a_v001.s	scr		

Activity	Command Checks	Date Done	Done By
Supporting Materials	 IBEX_CrossingTimes_<date>_v00x.txt on SFTP at /Archive- Incoming/IBEXIncoming/FDG/PredictedEphemeris/Orbit Events/.</date> Orbit Events File on SFTP at /IBEXOutgoing/MOC/Moc-Soc/oef/. Command Constraint Violations Report on SFTP at /IBEXOutgoing/MOC/Moc-Soc/cvr/. Contacts this orbit Orbit_oXXX.txt included in the ATS approval email. Science Tasking File at /Archive-Incoming/IBEXIncoming/MOC/Soc-Moc/stf/. Merged ATS at http://ibex.unh.edu/cgi-bin/ats.cgi. 	07/27/23	NGA
Sun Maneuvers	 Additional contacts <i>should not</i> be planned to support IBEX Sun Precession Maneuvers due to star tracker outages. The standard apogee and perigee contacts should be used to verify that a maneuver has occurred. If it is not possible to plan one of the standard contacts after the star tracker outage is down to 50% and a valid quaternion reading can be made to verify the maneuver, the coarse Sun sensor angle and the thruster pulse count will be used to determine a) whether a maneuver took place, and b) whether the pointing after the maneuver is as expected +/- 2 degrees. 	N/A	
	• The nominal off-Sun pointing constraint is 7.25 degrees. Based on the missed maneuver in orbit 114, the payload team has determined that there is no hardware risk associated with off-Sun pointing up to angles of at least 13 degrees. There is a higher background noted in the data starting at around 9.5 degrees off Sun pointing.		
File Input Check	 Current OEF inputs are Forecast STF, last orbit's OEF & latest predictive ephemeris. ATS inputs are this orbit's OEF & STF. (And ABS if present.) ATS filename is of the format IBEX_yyyy_doy_o0xxxa_v0zz.scr. where IBEX is capitalized, yyyy is the year, doy is the day of year, xxx is the 3-digit orbit number and zz is the 2-digit version number. Any special operations ATSs will have another designation between the orbit number and version number (i.e. *00186a_hgc_v001 for the Hi gain curve). 	07/27/23	NGA

IBEX Command Approval Checklist K. Fairchild

	1			
Eclipses	1.	Check OEF for eclipses during the orbit.	N/A	
	2.	Verify long eclipse flag start & stop times reflect Ryan Tyler's recommendations based on his		
		eclipse diagnostic tool. Suggestions made by Ryan after the use of this tool trump the general		
		guidelines below. (Please note, specific timing may shift if the recommendations are relative to		
		eclipse timing. For example, it may say set LE flag to false X hours after the end of the eclipse		
		with a given FALSE time suggested. If the eclipse timing changes as the ephemeris becomes		
		more refined, this command time may shift.)		
	3.	Verify no contacts planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
		recommendations will trump the general guidelines below.		
		a Verify transmitter OFF from 30 minutes before eclipse start through the end of the		
		eclipse.		
		b For an eclipse where the long eclipse flag is set, schedule a SOH contact directly		
		following the end of the eclipse (or per Ryan's assessment).		
		c Set the LE flag according to Ryan's assessments.		
	4.	Verify no maneuver planned during an eclipse. Note: If in conflict, the eclipse diagnostic		
		recommendations will trump the general guidelines below. a Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through		
		a Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through 3 hours after eclipse end.		
		b Verify no maneuver or cat bed heaters are on while the long eclipse flag is set.		
	5.	Verify the following additional constraints (from battery balancing section).		
	0.	a Verify the first command sets the long eclipse flag to TRUE, the second command		
		sets the flag to FALSE.		
		-		
		b Verify P/L is in HVSTANDBY or HVENG.		
		c Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro		
		execution.		
		This applies to all eclipses, not just moderate or long eclipses.		
Contact	1.	Verify STX on/off times, downlink rate against Orbit_oXXX.txt file.	07/27/23	NGA
Commands	2.	Verify contacts in the previous ATS have not been duplicated.		-
	3.	Verify all currently planned contacts in Orbit_xxx.txt are in the ATS.		
	4.	Verify each contact contains the following 5 commands.		
		SetRelay stx,on		
		• SetDownlink2K (2K, 40K, 64K, 160K, or 320K)		
		SetBilevelOutputControlReg STXMODE_Strobe,ON		
		SetBilevelOutputControlReg COHERENT,ON		
		SetRelay stx,off		
	5.	If contact is near an eclipse		
		a. Verify transmitter OFF from 30 minutes before eclipse start through 30 minutes after eclipse		
		end.		
		b. If additional transmitter constraints exist, they will be captured in Ryan's recommendations.		
	6.	If an APL contact is being used for an SSR Dump, the data rate should be at least 160 ksps & the SSR		
	0.	DUMP_NEW command should be included in the contact commands. Commands in Orange should only		
		be sent if the SSR pointers need to be reset this perigee. These commands should be separated by 2s and		
		occur 2s after the SSR_DUMP_NEW command.		
		SetRelay stx,on		
		SetDownlink2K		
		SetBilevelOutputControlReg STXMODE_Strobe,ON		
		SetBilevelOutputControlReg COHERENT,ON		
		SetDownlink320K		
		SSR_DUMP_NEW SSR_SET_RD_RTR_20000		
		SSR_SET_RD_PTR 70000		
		SSR_SET_WRT_PTR 70000		
		SetRelay stx,off		

IBEX Command Approval Checklist K. Fairchild

		07/07/00	
SC State	1. Transition to Science state will be first command of each ATS (at 14 Re).	07/27/23	NGA
Science: arc a	 SetScState science \$TIME=2023/08:07:11:32:55 		
arca	2. Lo science mode will be the next command (at 14 Re).		
	LO_SCIENCE_MODE NORMAL		
	3. Verify no transition to Science again at the end of the ATS. The ATS commands go from 14 Re to		
	14 Re in each orbit.		
	4. Verify the transition to Science commands for this orbit are not part of the previous ATS using		
	http://ibex.unh.edu/cgi-bin/ats.cgi.		
	5. Verify that the beginning of this ATS does not overlap with the end of the previous orbit's ATS		
	using http://ibex.unh.edu/cgi-bin/ats.cgi.		
Payload	1. Verify w/ Crossing Times report that it occurs about 15 Re ascending. The arc a ASCENDING	07/27/23	NGA
Mode	commands can start any time at or above 15 Re ascending.	01/21/20	i i on i
HVSCI :	2. Verify commanding takes ~ 24 minutes.		
arc a	• ASCENDING_PL1 \$TIME=2023/08:07:13:27:49		
	ASCENDING_HI		
	SET_PARAMETER 1, TLM_RATE_SOH		
	SET_PARAMETER 4, HV_STEP_DWELL		
	SET_PARAMETER 3, HV_STEP_FRAC		
	 HI_COL_NEG_LVL 1400 		
	• CEU_HI_CEM_1_LVL 1780		
	• CEU_HI_CEM_2_LVL 1780		
	• CEU_HI_CEM_3_LVL 1780		
	• CEU HI CEM 4 LVL 1900		
	• SET PARAMETER 0, TLM RATE SOH		
	ASCENDING PL2		
	ASCENDING_PL1		
	ASCENDING_LO		
	SET_PARAMETER 1, TLM_RATE_SOH_LO		
	SET_PARAMETER 4, HV_STEP_DWELL		
	SET_PARAMETER 1, HV_STEP_FRAC		
	CEU_LO_IF_MCP_VSET 2901		
	SET_PARAMETER 0, TLM_RATE_SOH_LO		
	 ASCENDING_PL2 \$TIME=2023/08:07:13:52:08 		
Payload	1. Payload DESCENDING commands end 1.5h before thruster enable.	07/27/23	NGA
Mode	 Verify commands take ~23 minutes to execute. 		
HVSTANDBY	 DESCENDING_PL1 \$TIME=2023/08:11:03:47:05 		
: arc a	DESCENDING_LO		
	• ASCENDING_PL2		
	• DESCENDING PL1		
	• DESCENDING HI		
	• DESCENDING PL2 \$TIME=2023/08:11:04:09:55		
	1. Spacecraft Housekeeping command occurs 1h before thruster enable.		
SC State		07/27/23	NGA
HK : arc a	 SetScState housekeeping \$TIME=2023/08:11:04:43:05 		

IBEX Command Approval Checklist K. Fairchild

Rev 17 Last update 11/05/2022

Inertial	1.	Use this command sequence if an apogee inertial maneuver is used, otherwise skip to the 'Sun Precession Maneuver : Apogee' sequence below.	07/27/23	NGA
Maneuver :	2	Verify Thruster enable command occurs within STF maneuver window.	1	
Apogee	2.			
		Verify no eclipse occurs from cat bed heater on through set FC mode Mission. Verify cat bed heaters come on 55 min before burn.		
	4.	-		
	-	CATBED_5N_HTR,ON \$TIME=2023/08:11:04:48:03 Varify Kalman Filter input called in ground command 8 actimates under in dischlord		
	5.	Verify Kalman Filter input select is ground command & estimator update is disabled.		
		 SetKFInputSelect GND_CMD, 0, 0, 0, 0 		
		 SetEstUpdateEnables ENABLE, DISABLE 		
	6.	Verify in FC mode Burn.		
		SetFcMode burn		
	7.	Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors match.		
		• SetInrDir -0.719652,0.640917,0.26707		
		targetX:-0.71965199999999996 targetY:0.64091699999999996		
		targetZ:0.2670699999999997		
	8.	Verify inertial maneuver chosen.		
		SetLrTarget ACS_INERTIAL		
	9.	Verify thrust time set to 11 min.		
		SetThrustTime 660		
	10.	 Verify thruster enable command matches RepointingManeuverStart time in OEF. SetThrustEnable ENABLE \$TIME=2023/08:11:05:43:03 		
		 RepointingManeuverStart 2023-08-11T05:43:03 		
	11.	Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0.		
		 SetThrustEnable DISABLE \$TIME=2023/08:11:05:53:03 		
		SetHTRCmd CATBED_5N_HTR,OFF		
		SetThrustTime 0		
	12.	 Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. SetStaticZrate ESTIMATOR, 0.418 \$TIME=2023/08:11:06:08:13 		
		SetKFInputSelect STA_PCT_VALID, 43,28,33,48		
		SetFcMode Mission		
Sun	1.	Use this command sequence in the event of an apogee Sun maneuver.	N/A	
Precession	2.	Verify Thruster enable command occurs within STF maneuver window.	N/A	
Maneuver	3.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission.		
	4.	Verify cat bed heaters powered on 55 min before thruster enable.		
: Apogee		CATBED 5N HTR,ON		
	5.	Verify in FC mode Burn and Sun target.		
	J.	SetFcMode burn	1	
		SetLrTarget ACS_SUN	1	
	c			
	6.	Verify thrust time set to 16 min. SetThrustTime 960 		
	-			
	7.	 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE 		
		SunMvrBegin		
	0	0		
	8.	Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0, FC mode Mission.	1	
		SetThrustEnable DISABLE	1	
		SetHTRCmd CATBED_5N_HTR,OFF	1	
		SetThrustTime 0	1	
	1	SetFcMode Mission		
SC Stata	1.	Spacecraft Science commands occur ~1h after thruster Disable.	07/07/00	NO
SC State Science :	1.	 Spacecraft Science commands occur ~1h after thruster Disable. SetScState science \$TIME=2023/08:11:06:58:09 	07/27/23	NG

IBEX Command Approval Checklist K. Fairchild

Payload Mode HVSCI : arc b	 Verify payload ASCENDING commands begin at least 1.5 hours after thruster DISABLE. Verify commands take ~24 minutes to execute. ASCENDING_PL1 \$TIME=2023/08:11:07:28:09 ASCENDING_HI SET_PARAMETER 1, TLM_RATE_SOH SET_PARAMETER 4, HV_STEP_DWELL SET_PARAMETER 3, HV_STEP_FRAC HI_COL_NEG_LVL 1400 CEU_HI_CEM_1_LVL 1780 CEU_HI_CEM_2_LVL 1780 CEU_HI_CEM_3_LVL 1780 CEU_HI_CEM_4_LVL 1900 SET_PARAMETER 0, TLM_RATE_SOH ASCENDING_PL2 ASCENDING_PL1 ASCENDING_PL1 SET_PARAMETER 1, TLM_RATE_SOH_LO SET_PARAMETER 1, TLM_RATE_SOH_LO SET_PARAMETER 1, TLM_RATE_SOH_LO SET_PARAMETER 1, HV_STEP_DWELL SET_PARAMETER 1, TLM_RATE_SOH_LO SET_PARAMETER 1, HV_STEP_FRAC CEU_LO_IF_MCP_VSET 2901 SET_PARAMETER 0, TLM_RATE_SOH_LO 	07/27/23	NGA
Payload Mode HVSTANDBY : arc b	 ASCENDING_PL2 \$TIME=2023/08:11:07:52:28 Verify W/ Crossing Times report that it occurs about 15 Re descending. The arc b DESCENDING commands can complete any time at or above 15 Re descending. Verify commands take ~23 minutes to execute. DESCENDING_PL1 \$TIME=2023/08:15:18:04:20 DESCENDING_LO ASCENDING_PL2 DESCENDING_PL1 DESCENDING_PL1 DESCENDING_HI DESCENDING_PL2 \$TIME=2023/08:15:18:27:10 	07/27/23	NGA
SC State HK : arc b	 Verify with Crossing Times report that Transition to Housekeeping state occurs at 14 Re desc (or an hour before the maneuver if the maneuver occurs less than 1 hour after 14 Re desc). SetScState housekeeping \$TIME=2023/08:15:20:00:06 	07/27/23	NGA

IBEX Command Approval Checklist K. Fairchild

Inertial Maneuver :	1.	Use this command sequence if a perigee inertial maneuver is used, otherwise skip to the 'Sun Precession Maneuver : Perigee' sequence below.	N/A	
Perigee	2.	Verify no eclipse occurs from cat bed heater on through set FC mode Mission.		
i ongoo	3.	Verify cat bed heaters come on 55 min before burn.		
		 CATBED_5N_HTR,ON \$TIME=2023/08:15:20:09:05 		
	4.	Verify in Housekeeping state.		
	5.	Verify Kalman Filter input select is ground command & estimator update is disabled.		
		 SetKFInputSelect GND_CMD, 0, 0, 0, 0 		
		SetEstUpdateEnables ENABLE, DISABLE		
	6.	Verify in FC mode Burn.		
	_	SetFcMode burn		
	7.	Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match.		
		• SetInrDir -0.770887,0.58794,0.24507		
		<pre>targetX:-0.770886999999999991targetY:0.58794000000000021</pre>		
		targetZ:0.2450700000000001		
		Verify inertial maneuver chosen.		
		SetLrTarget ACS_INERTIAL		
	8.	Verify thrust time set to 11 min.		
	0.	SetThrustTime 660		
	9.	Verify thruster enable command matches RepointingManeuverStart time in OEF.		
	5.	SetThrustEnable ENABLE \$TIME=2023/08:15:21:04:05		
	10	RepointingManeuverStart 2023-08-15T21:04:05		
	10.	Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0.		
		SetThrustEnable DISABLE \$TIME=2023/08:15:21:14:05		
		• CATBED_5N_HTR,OFF		
		SetThrustTime 0		
	11.	Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission.		
		 SetStaticZrate ESTIMATOR, 0.418 \$TIME=2023/08:15:21:29:15 		
		 SetKFInputSelect STA_PCT_VALID, 43,28,33,48 		
		SetFcMode Mission		
_	1.	Use this command sequence in the event of a perigee Sun maneuver.		
Sun	2.	Verify Thruster enable command occurs within STF maneuver window.	N/A	
Precession		Verify no eclipse occurs from cat bed heater on through set FC Mode Mission.		
Maneuver :		Verify cat bed heaters come on 55 min before burn.		
Perigee		CATBED_5N_HTR,ON		
	5	Verify in FC mode Burn and Sun target.		
	0.	SetFcMode burn		
		SetLrTarget ACS_SUN		
	6	Verify thrust time set to 16 min.		
	0.	SetThrustTime 960		
	7	Verify thruster enable command matches SunMvrBegin time in OEF.		
	1.	SetThrustEnable ENABLE		
	Q	SunMvrBegin Vorify 15 minutes after thrusters enabled: thrusters disabled, set had beaters off, thrust time set		
	ö.	Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set		
		to 0, FC mode Mission.		
		SetThrustEnable DISABLE		
		SetHTRCmd CATBED_5N_HTR,OFF		
		SetThrustTime 0		
		SetFcMode Mission	1	

IBEX Command Approval Checklist K. Fairchild

Battery Cell Balancing		07/27/23	NGA
Cmd Violation	1. Review CCVR. If you have any questions Reply All to the ATS Approval email and ask the team.	07/27/23	NGA

Activity	Anomaly Response : Non-nominal burn	Date Completed	Completed By
	 If the maneuver has not occurred or the spacecraft pointing as designated by either the star tracker or coarse Sun sensor is off by more than 2 degrees from the expected pointing, an enemaly has accurred 		
	 anomaly has occurred. If the spacecraft is in Contingency state all stored commands are flushed from the command queue. Follow standard anomaly process. 		
	 If the Sun maneuver did not occur and the spacecraft is in either Science or Housekeeping state follow the steps below. 		
	 If a partial Sun maneuver has occurred and the spacecraft is in either Science or Housekeeping state follow the steps below. 		
	 Please note that there is no anticipated hardware damage associated with exceeding the 12.5 degree constraint; this constraint is in place because we should not exceed the largest pointing achieved thus far in the mission. 		
	1. If the payload is in HVSTANDBY, LVENG or OFF, and there are no commands loaded to bring it to HVSCI voltages, no operational pointing constraints will be violated. Follow standard anomaly process.		
	 If the payload is in HVSCI mode or there are uploaded commands to bring the payload to HVSCI mode, 		
	 a. Determine current off Sun pointing. If the off Sun angle has already exceeded 12.5 degrees, the MOC should notify the MOM and immediately send the DESCENDING command suite in real-time, as described below. If this cannot be done in the contact where the pointing anomaly was discovered, another contact will be planned as soon as possible to execute these commands. @CEU_MACRO_EXEC DESCENDING_PL1 (<1 min) @CEU_MACRO_EXEC DESCENDING_LO (~10 min) @CEU_MACRO_EXEC DESCENDING_HI (~8 min) @CEU_MACRO_EXEC DESCENDING_PL2 (<1 min) Please note: The only scenario where hitting 12.5 degrees is expected is when a perigee Sun precession maneuver is completely missed after an inertial apogee maneuver which occurs late in the maneuver window (near apoge + 10 hours). b. If current Sun pointing is below 12.5 degrees, the ISOC should input ST Sunpointing angle into ibex_rotate to determine the Sun angle at the time of DESCENDING. Sun-Angle at payload DESCENDING		
	 d. If 12.5 degrees is exceeded by the time of DESCENDING, a new command set should be sent. i. The ISOC will generate the new STF which has the DESCENDING commands executing early such that 12.5 degrees is not exceeded while the payload is in HVSCI. ii. The MOC will create an associated ATS. iii. Approval is needed by the MOM, MOC & ISOC prior to upload. iv. The MOC will assess whether an additional pass is needed in order to upload the commands prior to exceeding the 12.5 degree constraint. The onboard DESCENDING commands do not need to be deleted. 		