IBEX Command Approval Checklist

| Rev 16h reduces batter | y cell balancing | offset from maneuvers |
|------------------------|------------------|-----------------------|
|------------------------|------------------|-----------------------|

| Orbit | 640 | Special Ops | | | |
|--------------------------------------|--|--------------------------|--------------------------------------|----------------------------|-----------------------|
| 14 R _E asc. Date/Time | 3/3/2024 11:0 | 05:01 | 15 R _E asc. Date/Time | 3/3/2024 12:50:04 | |
| Apogee | 3/7/2024 14:47:52 | Maneuver Window Start | 3/7/2024 04:50:12 | Maneuver Window End | 3/8/2024 00:50:14 |
| Apogee Target | targetX:0.9795230000000003 targetY:-0.1809070000000001 targetZ:-0.0883550000000000 | | | | |
| 15 R _E desc. Date/Time | 3/11/2024 16 | :19:51 | 14 R _E desc. Date/Time | 3/11/2024 18:03:07 | |
| Perigee | 3/12/2024 03:45:46 | Maneuver Window Start | 3/11/2024 18:35:29 | Maneuver Window Stop | 3/12/2024 13:31:28 |
| Perigee Target | <pre>targetX:0.992 targetZ:-0.058</pre> | | targetY:-0.1105 | 51400000000000000000 | |
| Eclipse | Yes | Eclipse Start | | Eclipse End | |
| Sun Mnvr | No | Apogee/Perigee | | Sun Angle at DESCENDING | |
| Approved Version | IBEX_2023_063 | _00640a_v001.s | scr | • | ч |

| Activity | Command Checks | Date Done | Done By |
|-------------------------|---|-----------|---------|
| Supporting Materials | IBEX_CrossingTimes_<date>_v00x.txt on SFTP at /Archive- Incoming/IBEXIncoming/FDG/PredictedEphemeris/Orbit Events/.</date> Orbit Events File on SFTP at /IBEXOutgoing/MOC/Moc-Soc/oef/. Command Constraint Violations Report on SFTP at /IBEXOutgoing/MOC/Moc-Soc/cvr/. Contacts this orbit Orbit_oXXX.txt included in the ATS approval email. Science Tasking File at /Archive-Incoming/IBEXIncoming/MOC/Soc-Moc/stf/. Merged ATS at http://ibex.unh.edu/cgi-bin/ats.cgi. | 02/22/24 | NGA |
| Sun Maneuvers | Additional contacts <i>should not</i> be planned to support IBEX Sun Precession Maneuvers due to star tracker outages. The standard apogee and perigee contacts should be used to verify that a maneuver has occurred. If it is not possible to plan one of the standard contacts after the star tracker outage is down to 50% and a valid quaternion reading can be made to verify the maneuver, the coarse Sun sensor angle and the thruster pulse count will be used to determine a) whether a maneuver took place, and b) whether the pointing after the maneuver is as expected +/- 2 degrees. The nominal off-Sun pointing constraint is 7.25 degrees. Based on the missed maneuver in orbit 114, the payload team has determined that there is no hardware risk associated with off-Sun pointing up to angles of at least 13 degrees. There is a higher background noted in the data starting at around 9.5 degrees off Sun pointing. | N/A | NGA |

| File Input Check | Current OEF inputs are Forecast STF, last orbit's OEF & latest predictive ephemeris. ATS inputs are this orbit's OEF & STF. (And ABS if present.) ATS filename is of the format IBEX_yyyy_doy_o0xxxa_v0zz.scr. where IBEX is capitalized, yyyy is the year, doy is the day of year, xxx is the 3-digit orbit number and zz is the 2-digit version number. Any special operations ATSs will have another designation between the orbit number and version | 02/22/24 | NGA |
|---------------------|--|--------------------|-----|
| | number (i.e. *o0186a_hgc_v001 for the Hi gain curve). | | |
| Eclipses | 1. Check OEF for eclipses during the orbit. | 02/22/24 | NGA |
| | Verify long eclipse flag start & stop times reflect Ryan Tyler's recommendations based on his eclipse diagnostic tool. Suggestions made by Ryan after the use of this tool trump the general guidelines below. (Please note, specific timing may shift if the recommendations are relative to | Short penumbral | |
| | eclipse timing. For example, it may say set LE flag to false X hours after the end of the eclipse with a given FALSE time suggested. If the eclipse timing changes as the ephemeris becomes more refined, this command time may shift.) | No action required | |
| | Verify no contacts planned during an eclipse. Note: If in conflict, the eclipse diagnostic recommendations will trump the general guidelines below. a Verify transmitter OFF from 30 minutes before eclipse start through the end of the eclipse. | | |
| | b For an eclipse where the long eclipse flag is set, schedule a SOH contact directly following the end of the eclipse (or per Ryan's assessment). c Set the LE flag according to Ryan's assessments. | | |
| | Verify no maneuver planned during an eclipse. Note: If in conflict, the eclipse diagnostic recommendations will trump the general guidelines below. a Verify no maneuver or cat bed heaters on from 3 hours before eclipse start through 3 hours after eclipse end. | | |
| | b Verify no maneuver or cat bed heaters are on while the long eclipse flag is set. 5. Verify the following additional constraints (from battery balancing section). a Verify the first command sets the long eclipse flag to TRUE, the second command sets the flag to FALSE. | | |
| | b Verify P/L is in HVSTANDBY or HVENG. c Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution. | | |
| | This applies to all eclipses, not just moderate or long eclipses. | | |

| Contact Commands | Verify STX on/off times, downlink rate against Orbit_oXXX.txt file. Verify contacts in the previous ATS have not been duplicated. Verify all currently planned contacts in Orbit_xxx.txt are in the ATS. Verify each contact contains the following 5 commands. SetRelay stx,on SetBilevelOutputControlReg STXMODE_Strobe,ON SetRelay stx,off If contact is near an eclipse Verify transmitter OFF from 30 minutes before eclipse start through 30 minutes after eclipse end. If additional transmitter constraints exist, they will be captured in Ryan's recommendations. If an APL contact is being used for an SSR Dump, the data rate should be at least 160 ksps & the SSR DUMP_NEW command should be included in the contact commands. Commands in Orange should only be sent if the SSR pointers need to be reset this perigee. These commands should be separated by 2s and occur 2s after the SSR DUMP_NEW command. SetRelay stx,on SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg STXMODE_Strobe,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHERENT,ON SetBilevelOutputControlReg COHE | 02/22/24 | NGA |
|-------------------------------|--|----------|-----|
| | SSR_SET_RD_PTR 70000 SSR_SET_WRT_PTR 70000 SetRelay stx,off | | |
| SC State Science: arc a | Transition to Science state will be first command of each ATS (at 14 Re). SetScState science \$TIME=2024/03:03:11:05:15 Lo science mode will be the next command (at 14 Re). LO_SCIENCE_MODE NORMAL Verify no transition to Science again at the end of the ATS. The ATS commands go from 14 Re to 14 Re in each orbit. | 02/22/24 | NGA |
| | Verify the transition to Science commands for this orbit are not part of the previous ATS using <u>http://ibex.unh.edu/cgi-bin/ats.cgi</u>. Verify that the beginning of this ATS does not overlap with the end of the previous orbit's ATS using <u>http://ibex.unh.edu/cgi-bin/ats.cgi</u>. | | |

| Payload Mode HVSCI : arc a | Verify w/ Crossing Times report that it occurs about 15 Re ascending. The arc a ASCENDING commands can start any time at or above 15 Re ascending. Verify commanding takes ~ 24 minutes. ASCENDING_PL1_\$TIME=2024/03:03:12:50:16 ASCENDING_HI SET_PARAMETER 1, TLM_RATE_SOH SET_PARAMETER 3, HV_STEP_DWELL SET_PARAMETER 3, HV_STEP_FRAC HI_COL_NEG_LVL 1400 CEU_HI_CEM_1_LVL 1780 CEU_HI_CEM_2_LVL 1780 CEU_HI_CEM_4_LVL 1900 SET_PARAMETER 0, TLM_RATE_SOH ASCENDING_PL2 ASCENDING_PL1 ASCENDING_PL1 SET_PARAMETER 1, TLM_RATE_SOHLO SET_PARAMETER 1, HV_STEP_DWELL SET_PARAMETER 1, HV_STEP_DOWELL SET_PARAMETER 1, HV_STEP_FRAC CEU_LO_IF_MCP_VSET 2901 SET_PARAMETER 0, TLM_RATE_SOHLO ASCENDING_PL2 \$TIME=2024/03:03:13:14:35 | 02/22/24 | NGA |
|---|---|----------|-----|
| Payload Mode HVSTANDBY : arc a | Payload DESCENDING commands end 1.5h before thruster enable. Verify commands take ~23 minutes to execute. | 02/22/24 | NGA |
| SC State HK : arc a | Spacecraft Housekeeping command occurs 1h before thruster enable. SetScState housekeeping \$TIME=2024/03:07:03:50:14 | 02/22/24 | NGA |

| Inertial | 1. | Use this command sequence if an apogee inertial maneuver is used, otherwise skip to the 'Sun Precession Maneuver : Apogee' sequence below. | 02/22/24 | NGA |
|------------|-----|--|----------|------|
| Maneuver : | 2. | Verify Thruster enable command occurs within STF maneuver window. | | |
| Apogee | | Verify no eclipse occurs from cat bed heater on through set FC mode Mission. | | |
| | 4. | Verify cat bed heaters come on 55 min before burn. | | |
| | | CATBED_5N_HTR,ON \$TIME=2024/03:07:03:55:12 | | |
| | 5. | Verify Kalman Filter input select is ground command & estimator update is disabled. | | |
| | ••• | SetKFInputSelect GND_CMD, 0, 0, 0, 0 | | |
| | | SetEstUpdateEnables ENABLE, DISABLE | | |
| | 6. | Verify in FC mode Burn. | | |
| | 0. | SetFcMode burn | | |
| | 7. | Compare SetInrDir in ATS with pointing as defined in the Forecast STF & verify the vectors | | |
| | | match. | | |
| | | • SetInrDir 0.979523,-0.180907,-0.088355 | | |
| | | targetX:0.9795230000000003 targetY:-0.1809070000000001 | | |
| | | targetZ:-0.0883550000000000 | | |
| | 8. | Verify inertial maneuver chosen. | | |
| | 0. | SetLrTarget ACS_INERTIAL | | |
| | 9. | Verify thrust time set to 11 min. | | |
| | 5. | SetThrustTime 660 | | |
| | 10. | Verify thruster enable command matches RepointingManeuverStart time in OEF. | | |
| | | SetThrustEnable ENABLE \$TIME=2024/03:07:04:50:12 | | |
| | | RepointingManeuverStart 2024-03-07T04:50:12 | | |
| | 11 | Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set | | |
| | | to 0. | | |
| | | SetThrustEnable DISABLE \$TIME=2024/03:07:05:00:12 | | |
| | | | | |
| | | SetHTRCmd CATBED_5N_HTR,OFF | | |
| | | SetThrustTime 0 | | |
| | 12. | Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. | | |
| | | • SetStaticZrate ESTIMATOR, 0.418 \$TIME=2024/03:07:05:15:22 | | |
| | | SetKFInputSelect STA_PCT_VALID, 43,28,33,48 | | |
| | | SetFcMode Mission | | |
| Sun | 1. | Use this command sequence in the event of an apogee Sun maneuver. | N/A | |
| Precession | 2. | Verify Thruster enable command occurs within STF maneuver window. | - | |
| Maneuver | 3. | Verify no eclipse occurs from cat bed heater on through set FC mode Mission. | | |
| : Apogee | 4. | Verify cat bed heaters powered on 55 min before thruster enable. | | |
| | _ | • CATBED_5N_HTR,ON | | |
| | 5. | Verify in FC mode Burn and Sun target. | | |
| | | SetFcMode burn | | |
| | _ | SetLrTarget ACS_SUN | | |
| | 6. | Verify thrust time set to 16 min. | | |
| | _ | SetThrustTime 960 | | |
| | 7. | Verify thruster enable command matches SunMvrBegin time in OEF. | | |
| | | SetThrustEnable ENABLE | | |
| | _ | • SunMvrBegin | | |
| | 8. | Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set | | |
| | | to 0, FC mode Mission. | | |
| | | SetThrustEnable DISABLE | | |
| | | SetHTRCmd CATBED_5N_HTR,OFF | | |
| | | SetThrustTime 0 | | |
| | | SetFcMode Mission | ļ | |
| SC State | 1. | Spacecraft Science commands occur ~1h after thruster Disable. | 02/22/24 | NG/ |
| Science : | | SetScState science \$TIME=2024/03:07:06:05:18 | 02/22/24 | 110/ |
| | 1 | LO_SCIENCE_MODE NORMAL | 1 | 1 |

| Payload Mode HVSCI : arc b | Verify commands take ~24 minutes to execute. ASCENDING_PL1 \$TIME=2024/03:07:06:35:18 ASCENDING_HI SET_PARAMETER 1, TLM_RATE_SOH SET_PARAMETER 4, HV_STEP_DWELL SET_PARAMETER 3, HV_STEP_FRAC HI_COL_NEG_LVL 1400 CEU_HI_CEM_1_LVL 1780 CEU_HI_CEM_2_LVL 1780 CEU_HI_CEM_3_LVL 1780 CEU_HI_CEM_4_LVL 1900 SET_PARAMETER 0, TLM_RATE_SOH ASCENDING_PL2 ASCENDING_LO SET_PARAMETER 1, TLM_RATE_SOH_LO SET_PARAMETER 4, HV_STEP_DWELL SET_PARAMETER 4, HV_STEP_DWELL SET_PARAMETER 4, HV_STEP_FRAC CEU_LO_IF_MCP_VSET 2901 SET_PARAMETER 0, TLM_RATE_SOH_LO | 02/22/24 | NGA |
|---|---|----------|-----|
| Payload 1. Mode HVSTANDBY 2. : arc b | commands can complete any time at or above 15 Re descending. | 02/22/24 | NGA |
| SC State 1. HK : arc b | Verify with Crossing Times report that Transition to Housekeeping state occurs at 14 Re desc (or an hour before the maneuver if the maneuver occurs less than 1 hour after 14 Re desc). SetScState housekeeping \$TIME=2024/03:11:17:33:07 | 02/22/24 | NGA |

| Inertial Maneuver : | 1. | Use this command sequence if a perigee inertial maneuver is used, otherwise skip to the 'Sun Precession Maneuver : Perigee' sequence below. | N/A | |
|--------------------------|----------------------------------|--|----------|----|
| Perigee | 2. | Verify no eclipse occurs from cat bed heater on through set FC mode Mission. | | |
| i engee | 3. | Verify cat bed heaters come on 55 min before burn. | | |
| | | CATBED_5N_HTR,ON \$TIME=2024/03:11:21:21:49 | | |
| | 4. | Verify in Housekeeping state. | | |
| | | Verify Kalman Filter input select is ground command & estimator update is disabled. | | |
| | 5. | | | |
| | | SetKFInputSelect GND_CMD, 0, 0, 0, 0 | | |
| | _ | SetEstUpdateEnables ENABLE, DISABLE | | |
| | 6. | Verify in FC mode Burn. | | |
| | | SetFcMode burn | | |
| | 7. | Compare SetInrDir in ATS with target vector in the Forecast STF & verify the vectors match. | | |
| | | • SetInrDir 0.992133,-0.110514,-0.058819 | | |
| | | targetX:0.9921330000000004 targetY:-0.1105140000000000 | | |
| | | targetZ:-0.0588190000000000 | | |
| | | Verify inertial maneuver chosen. | | |
| | | SetLrTarget ACS_INERTIAL | | |
| | 8. | Verify thrust time set to 11 min. | | |
| | 0. | • | | |
| | | SetThrustTime 660 | | |
| | 9. | Verify thruster enable command matches RepointingManeuverStart time in OEF. | | |
| | | SetThrustEnable ENABLE \$TIME=2024/03:11:22:16:49 | | |
| | | RepointingManeuverStart 2024-03-11T22:16:49 | | |
| | 10. | Verify 10 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set | | |
| | | to 0. | | |
| | | SetThrustEnable DISABLE \$TIME=2024/03:11:22:26:49 | | |
| | | CATBED 5N HTR,OFF | | |
| | | SetThrustTime 0 | | |
| | 11 | Verify 25 min after thrusters enabled: Static Z rate set, outage %valid set, FC mode Mission. | | |
| | | SetStaticZrate ESTIMATOR, 0.418 \$TIME=2024/03:11:22:41:59 | | |
| | | | | |
| ļ | | | | |
| | | SetKFInputSelect STA_PCT_VALID, 43,28,33,48 | | |
| | | SetKFInputSelect STA_PCT_VALID, 43,28,33,48SetFcMode Mission | | |
| Sup | 1. | SetFcMode Mission | 02/22/24 | NC |
| Sun | | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. | 02/22/24 | NG |
| Precession | 2. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. | 02/22/24 | NG |
| Precession | 2. 3. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. 6. 7. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. 6. 7. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE SunMvrBegin | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. 6. 7. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE SunMvrBegin | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. 6. 7. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetFrarget ACS_SUN Verify thrust time set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE SunMvrBegin Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0, FC mode Mission. SetThrustEnable DISABLE | 02/22/24 | NG |
| Precession Maneuver : | 2. 3. 4. 5. 6. 7. | SetFcMode Mission Use this command sequence in the event of a perigee Sun maneuver. Verify Thruster enable command occurs within STF maneuver window. Verify no eclipse occurs from cat bed heater on through set FC Mode Mission. Verify cat bed heaters come on 55 min before burn. CATBED_5N_HTR,ON Verify in FC mode Burn and Sun target. SetFcMode burn SetLrTarget ACS_SUN Verify thrust ime set to 16 min. SetThrustTime 960 Verify thruster enable command matches SunMvrBegin time in OEF. SetThrustEnable ENABLE SunMvrBegin Verify 15 minutes after thrusters enabled: thrusters disabled, cat bed heaters off, thrust time set to 0, FC mode Mission. | 02/22/24 | NG |

| Battery C Balancir | | There will be battery cell balancing every 2 out of 3 orbits. Battery cell balancing this orbit? N Verify charging cycle (Long eclipse flag=TRUE) is 90 minutes long. Verify the first command sets the long eclipse flag to TRUE, the second command sets the flag to FALSE. Verify P/L is in HVSTANDBY or HVENG. (The DESCENDING_PL1 macro leaves us in HVENG; the DESCENDING_PL2 macro leaves us in HVSTANDBY.) Verify no charging cycle within 2 hours of ASCENDING or DESCENDING macro execution. Verify no charging cycle within 15 minutes of maneuver. Verify no charging cycle during an eclipse. | 02/22/24 | NGA |
|-----------------------|---------|--|----------|-----|
| Cmd Violatio | ן 1. | Review CCVR. If you have any questions Reply All to the ATS Approval email and ask the team. | 02/22/24 | NGA |

| Activity | Anomaly Response : Non-nominal burn | Date Completed | Completed By |
|----------|--|-------------------|-----------------|
| | If the maneuver has not occurred or the spacecraft pointing as designated by either the star tracker or coarse Sun sensor is off by more than 2 degrees from the expected pointing, an anomaly has occurred. If the spacecraft is in Contingency state all stored commands are flushed from the | | |
| | command queue. Follow standard anomaly process. | | |
| | If the Sun maneuver did not occur and the spacecraft is in either Science or Housekeeping state follow the steps below. | | |
| | If a partial Sun maneuver has occurred and the spacecraft is in either Science or Housekeeping state follow the steps below. | | |
| | • Please note that there is no anticipated hardware damage associated with exceeding the 12.5 degree constraint; this constraint is in place because we should not exceed the largest pointing achieved thus far in the mission. | | |
| | 1. If the payload is in HVSTANDBY, LVENG or OFF, and there are no commands loaded to bring it to HVSCI voltages, no operational pointing constraints will be violated. Follow | | |
| | standard anomaly process.2. If the payload is in HVSCI mode or there are uploaded commands to bring the payload to HVSCI mode, | | |
| | a. Determine current off Sun pointing. If the off Sun angle has already exceeded 12.5 degrees, the MOC should notify the MOM and immediately send the DESCENDING command suite in real-time, as described below. If this cannot be done in the contact where the pointing anomaly was discovered, another contact will be planned as soon as possible to execute these commands. @CEU_MACRO_EXEC DESCENDING_PL1 (<1 min) @CEU_MACRO_EXEC DESCENDING_LO (~10 min) @CEU_MACRO_EXEC DESCENDING_PL2 (<1 min) @CEU_MACRO_EXEC DESCENDING_PL2 (<1 min) Please note: The only scenario where hitting 12.5 degrees is expected is when a perigee Sun precession maneuver is completely missed after an inertial apogee maneuver which occurs late in the maneuver window (near apoge + 10 hours). b. If current Sun pointing is below 12.5 degrees, the ISOC should input ST Sunpointing angle into ibex_rotate to determine the Sun angle at the time of DESCENDING. Sun-Angle at payload DESCENDING C. If 12.5 degrees is not exceeded by the time of DESCENDING, no payload-specific action is needed for this arc. Follow standard anomaly response process. d. If 12.5 degrees is exceeded by the time of DESCENDING, a new command set | | |
| | should be sent. i. The ISOC will generate the new STF which has the DESCENDING commands executing early such that 12.5 degrees is not exceeded while the payload is in HVSCI. ii. The MOC will create an associated ATS. iii.Approval is needed by the MOM, MOC & ISOC prior to upload. iv.The MOC will assess whether an additional pass is needed in order to upload the commands prior to exceeding the 12.5 degree constraint. The onboard DESCENDING commands do not need to be deleted. | | |